

Single-Fiber Tight-Buffered Cable, Riser

2.9 mm diameter, SMF-28® Ultra fiber, Single-mode (OS2)

CORNING

Corning single-fiber cables are designed for interconnect applications. A 900 µm buffered fiber is surrounded by aramid yarn strength members and a flame-retardant jacket. Dielectric strength members offer mechanical durability and the flame-resistant jacket meet requirements of the National Electrical Code® (NEC®) Article 770.

This cable is available in 12 different jacket colors – blue, orange, green, brown, slate, white, red, black, yellow, violet, rose and aqua. The colored jacket allows for easy visual identification of the cables. The standard jacket color will be determined by the dominant fiber type in the cable and will use the standard part numbers shown here. Contact Customer Care at 1-800-743-2675 to order other color options.

Features and Benefits

Meets NEC requirements

Meets burn test criteria

All-dielectric strength member

Mechanical durability


Standards

Listings

National Electrical Code® (NEC®) OFNR, FT-4

Design and Test Criteria

UL-1666 and CSA FT-4 (for riser and general building applications); ICEA S-83-596



Specifications

General Specifications	
Environment	Indoor
Application	General Purpose Horizontal, Vertical Riser
Cable Type	Tight-Buffered
Flame Rating	Riser (OFNR)

CORNING

Single-Fiber Tight-Buffered Cable, Riser

2.9 mm diameter, SMF-28® Ultra fiber, Single-mode (OS2)

CORNING

General Specifications

Fiber Category	SMF-28® Ultra fiber
Product Type	Interconnect

Temperature Range

Storage	-40 °C to 70 °C (-40 °F to 158 °F)
Operation	0 °C to 70 °C (32 °F to 158 °F)

Cable Design

Fiber Count	1
Tight Buffer Color	White
Tensile Strength Elements and/or Armoring - Layer 1	Dielectric strength members
Outer Jacket Material	Flame-retardant
Outer Jacket Color	Yellow

Mechanical Characteristics Cable

Nominal Outer Diameter	2.9 mm (0.11 in)
Weight	6.5 kg/km (4.4 lb/1000 ft)
Max. Tensile Strength, Short-Term	220 N (50 lbf)
Max. Tensile Strength, Long-Term	66 N (15 lbf)
Min. Bend Radius Installation	43.5 mm (1.7 in)
Min. Bend Radius Operation	7.5 mm (0.30 in)

Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

Fiber Specifications

Optical Characteristics (cabled)

Fiber Name	SMF-28® Ultra fiber
Fiber Category	G.652.D/G.657.A1
Fiber Code	Z
Performance Option Code	31

Single-Fiber Tight-Buffered Cable, Riser

2.9 mm diameter, SMF-28® Ultra fiber, Single-mode (OS2)



Fiber Specifications

Optical Characteristics (cabled)	
Wavelengths	1310 nm / 1383 nm / 1550 nm
Maximum Attenuation	0.65 dB/km / 0.65 dB/km / 0.5 dB/km

Ordering Information

Part Number	001Z31-31131-24
Product Description	Single-Fiber Tight-Buffered Cable, Riser, 2.9 mm diameter, SMF-28® Ultra fiber, Single-mode (OS2)
EAN Code	4056418139746



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2016 Corning Optical Communications. All rights reserved.

