

Reel In A Box, FREEDM® Fan-Out Tight-Buffered Cable, Riser

2 F, Single-mode (OS2)

CORNING

Reel in a Box is Corning's innovative packaging solution for small reels of fiber optic cable in all inside plant applications, such as collocation data centers and wireless projects. This packaging solution provides features that enable our customers greater efficiencies than before.

Corning FREEDM® fan-out cables are designed for routing inside and outside buildings into riser spaces, to security, surveillance or monitoring cameras, and within telecommunications rooms and workstations. With no need for transition splices when entering a building, this cable provides low-fiber-count connections within building backbone riser and horizontal spaces. The indoor/outdoor temperature and water-resistant performance provides superior protection for applications, like traffic control, with optical feeds in rugged environments.

Ideal for providing direct optical connections from indoor and outdoor surveillance cameras to security control locations, these cables can also provide a secure link for surveillance or data. The flame-retardant, 900 µm TBII Buffered Fibers are available in single-mode and multi-mode and enable easy, consistent stripping while the 2.0 mm subunits enable easy field terminations.

The fibers are surrounded by water-resistant, dielectric strength members and protected by a flexible, flame-retardant outer jacket. These cables meet the application requirements of the National Electrical Code (NEC Article 770) and are OFNR and FT-4 listed and comply with the ICEA S-104-696 tests. The all-dielectric cable construction requires no grounding or bonding, and the small diameter and bend radius allow easy installation in space-constrained areas. FREEDM fan-out cables are also available with approval for TEMPEST applications.



Features and Benefits

"Countdown" print indicates available cable remaining on the reel providing easier inventory management

Stackable boxes make storage more manageable

Smaller reel offerings mean smaller cable lengths than would normally be available

Cable cutting at Corning lowers operating expenses for our distributors and end users



Reel In A Box, FREEDM® Fan-Out Tight-Buffered Cable, Riser

2 F, Single-mode (OS2)

CORNING

Standards

Approvals and Listings	National Electrical Code® (NEC®) OFNR, CSA OFN FT-4
Design and Test Criteria	ICEA S-104-696
Flame Resistance	UL-1666 (for riser and general building applications)

Specifications

General Specifications	
Environment	Indoor/Outdoor
Application	Direct Buried, Duct, General Purpose Horizontal, Vertical Riser
Cable Type	Tight-Buffered
Product Type	Dielectric
Flame Rating	Riser (OFNR)
Fiber Category	Single-mode (OS2)
Fiber Length	150 m (500 ft)

Temperature Range	
Storage	-40 °C to 70 °C (-40 °F to 158 °F)
Installation	-10 °C to 70 °C (14 °F to 158 °F)
Operation	-40 °C to 70 °C (-40 °F to 158 °F)

Cable Design	
Central Element	Dielectric
Fiber Count	2
Fiber Coloring	Yellow
Fibers per Tube	1
Number of Tube Positions	4
Number of Active Tubes	2
Buffer Tube Color Coding	Yellow
Buffer Tube Diameter	2.0 mm (0.08 in)
Outer Jacket Material	Flame-Retardant, UV-Resistant
Outer Jacket Color	Black

Reel In A Box, FREEDM® Fan-Out Tight-Buffered Cable, Riser

2 F, Single-mode (OS2)

CORNING

Mechanical Characteristics Cable

Max. Tensile Strength, Short-Term	660 N (150 lbf)
Max. Tensile Strength, Long-Term	330 N (75 lbf)
Weight	39 kg/km (86 lb/1000 ft)
Nominal Outer Diameter	6.8 mm (0.27 in)
Min. Bend Radius Installation	102 mm (4.1 in)
Min. Bend Radius Operation	68 mm (2.7 in)

Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

Fiber Specifications

Optical Characteristics (cabled)

Fiber Name	SMF-28e® fiber
Fiber Category	G.652.D
Fiber Code	E
Performance Option Code	31
Wavelengths	1310 nm / 1383 nm / 1550 nm
Maximum Attenuation	0.65 dB/km / 0.65 dB/km / 0.50 dB/km

Ordering Information

Part Number	002E6F-31331-B1
Product Description	Reel in a Box, FREEDM® Fan-Out Tight-Buffered Cable, Riser, 2 F, Single-mode (OS2)
EAN Code	4056418139371

Shipping Information

Packaging Method	Reel In A Box
Dimensions (HxWxD)	39.37 cm x 39.37 cm x 38.73 cm (15.5 in x 15.5 in x 15.25 in)

Reel In A Box, FREEDM[®] Fan-Out Tight-Buffered Cable, Riser

2 F, Single-mode (OS2)

The CORNING logo is displayed in white, uppercase letters within a solid blue square.

Notes



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks.

All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2017 Corning Optical Communications. All rights reserved.