

# Reel In A Box, Zipcord Tight-Buffered Cable, Plenum

2 F, 50  $\mu$ m multimode, extended 10G distance (OM4)

CORNING

Reel in a Box is Corning's innovative packaging solution for small reels of fiber optic cable in all inside plant applications, such as collocation data centers and wireless projects. This packaging solution provides features that enable our customers greater efficiencies than before.

Corning zipcord cables are designed for interconnect applications. Two 900  $\mu$ m buffered fibers are surrounded by aramid yarn strength members and a flame-retardant jacket. This cable design offers mechanical durability and flame resistance that meet the requirements of the National Electrical Code® (NEC®) Article 770.

## Features and Benefits

"Countdown" print indicates available cable remaining on the reel providing easier inventory management

Stackable boxes make storage more manageable


Smaller reel offerings mean smaller cable lengths than would normally be available

Cable cutting at Corning lowers operating expenses for our distributors and end users

## Standards

**Approvals and Listings** National Electrical Code® (NEC®) OFNP, CSA FT-6, ICEA S-83-596

**Flame Resistance** NFPA 262 (for plenum, riser and general building applications)



## Specifications

General Specifications	
Environment	Indoor
Application	General Purpose Horizontal, Vertical Riser, Plenum
Cable Type	Tight-Buffered
Product Type	Interconnect

# Reel In A Box, Zipcord Tight-Buffered Cable, Plenum

2 F, 50 µm multimode, extended 10G distance (OM4)

CORNING

## General Specifications

Flame Rating	Plenum (OFNP)
Fiber Category	50 µm MM (OM4+)
Fiber Length	900 m (3000 ft)

## Temperature Range

Storage	-40 °C to 70 °C (-40 °F to 158 °F)
Operation	0 °C to 70 °C (32 °F to 158 °F)

## Cable Design

Fiber Count	2
Tight Buffer Color	Blue, White
Tensile Strength Elements and/or Armoring - Layer 1	Dielectric strength members
Number of Subunits	2
Outer Jacket Material	Flame-retardant
Outer Jacket Color	Aqua

## Mechanical Characteristics Cable

Max. Tensile Strength, Short-Term	220 N (50 lbf)
Max. Tensile Strength, Long-Term	66 N (15 lbf)
Weight	5 kg/km (3.5 lb/1000 ft)
Nominal Outer Diameter	1.6 mm x 3.3 mm (0.06 in x 0.13 in)
Min. Bend Radius Installation	50 mm (2 in)
Min. Bend Radius Operation	8 mm (0.3 in)

## Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	-----------------------------------------------------------

## Fiber Specifications

### Optical Characteristics (cabled)

Fiber Core Diameter	50 µm
Fiber Category	OM4 Extended Distance

# Reel In A Box, Zipcord Tight-Buffered Cable, Plenum

2 F, 50  $\mu$ m multimode, extended 10G distance (OM4)



## Fiber Specifications

Optical Characteristics (cabled)	
Fiber Code	T
Performance Option Code	91
Wavelengths	850 nm / 1300 nm
Maximum Attenuation	2.8 dB/km / 1.0 dB/km
Serial 1 Gigabit Ethernet	1100 m / 600 m
Serial 10 Gigabit Ethernet	600 m / -
Min. Overfilled Launch (OFL) Bandwidth	3500 MHz*km / 500 MHz*km
Minimum Effective Modal Bandwidth (EMB)	5350 MHz*km / -

## Ordering Information

Part Number	002T58-31491-B5
Product Description	Reel in a Box, Zipcord Tight-Buffered Cable, Plenum, 2 F, 1.6 mm diameter, 50 $\mu$ m multimode, extended 10G distance (OM4)
EAN Code	4056418146539

## Shipping Information

Packaging Method	Reel In A Box
Dimensions (HxWxD)	39.37 cm x 39.37 cm x 38.73 cm (15.5 in x 15.5 in x 15.25 in)



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • [www.corning.com/opcomm](http://www.corning.com/opcomm)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/trademarks](http://www.corning.com/opcomm/trademarks). All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2018 Corning Optical Communications. All rights reserved.