

MIC[®] Tight-Buffered Cable, Plenum

6 F, Single-mode (OS2)

CORNING

Corning MIC[®] plenum cables are designed for use in plenum, riser and general purpose environments for intrabuilding backbone and horizontal installations. These multifiber cables use 900 μm buffered fibers to allow easy, consistent stripping and to facilitate termination. The fibers are surrounded by dielectric strength members and protected by a flame-retardant outer jacket.

The all-dielectric cable construction requires no grounding or bonding. MIC plenum cables are ideal for routing inside buildings, within plenum areas and riser shafts, to the telecommunications rooms and workstations. The MIC plenum cables meet the application requirements of the National Electrical Code[®] (NEC[®]) Article 770 and are OFNP and FT-6 listed.

This cable is available in 12 different jacket colors – blue, orange, green, brown, slate, white, red, black, yellow, violet, rose and aqua. The colored jacket allows for easy visual identification of the cables. The standard jacket color will be determined by the dominant fiber type in the cable and will use the standard part numbers shown here. Contact Customer Care at 1-800-743-2675 to order other color options.

Features and Benefits

900 μm buffered fibers

Easy, consistent stripping

All-dielectric construction

Requires no grounding or bonding

Flame-retardant jacket

Rugged and durable


Standards

Listings

National Electrical Code[®]
(NEC[®]) OFNP, FT-6

Design and Test Criteria

NFPA 262 and CSA FT-6
(for plenum, riser and general building applications);
ICEA S-83-596



MIC[®] Tight-Buffered Cable, Plenum

6 F, Single-mode (OS2)

CORNING

Specifications

General Specifications	
Environment	Indoor
Application	General Purpose Horizontal, Vertical Riser, Plenum
Cable Type	Tight-Buffered
Product Type	Distribution
Flame Rating	Plenum (OFNP)
Fiber Category	Single-mode (OS2)

Temperature Range	
Storage	-40 °C to 70 °C (-40 °F to 158 °F)
Installation	0 °C to 60 °C (32 °F to 140 °F)
Operation	0 °C to 70 °C (32 °F to 158 °F)

Cable Design	
Central Element	Yarn
Fiber Count	6
Tight Buffer Color	Blue, Orange, Green, Brown, Slate, White
Tensile Strength Elements and/or Armoring - Layer 1	Dielectric strength members
Outer Jacket Material	Flame-retardant
Outer Jacket Color	Yellow

Mechanical Characteristics Cable	
Max. Tensile Strength, Short-Term, ≤12F	440 N (100 lbf)
Max. Tensile Strength, Short-Term, >12F	660 N (150 lbf)
Max. Tensile Strength, Long-Term, ≤12F	132 N (30 lbf)
Max. Tensile Strength, Long-Term, >12F	200 N (45 lbf)
Nominal Outer Diameter	5.2 mm (0.21 in)
Weight	24.2 kg/km (16.3 lb/1000 ft)
Min. Bend Radius Installation	78 mm (3.1 in)
Min. Bend Radius Operation	52 mm (2.1 in)

MIC[®] Tight-Buffered Cable, Plenum

6 F, Single-mode (OS2)



Fiber Specifications

Optical Characteristics (cabled)	
Fiber Name	SMF-28e [®] fiber
Fiber Category	G.652.D
Fiber Code	E
Performance Option Code	31
Wavelengths	1310 nm / 1383 nm / 1550 nm
Maximum Attenuation	0.4 dB/km / 0.4 dB/km / 0.4 dB/km

Ordering Information

Part Number	006E88-31131-29
Product Description	MIC [®] Tight-Buffered Cable, Plenum, 6 F, Single-mode (OS2)
EAN Code	4056418191256



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks.

All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2018 Corning Optical Communications. All rights reserved.

