

FREEDM[®] Loose Tube, Gel-Free, Interlocking Armored Cable, Plenum

12 F, 50 μm multimode (OM2)

CORNING

Corning FREEDM[®] loose tube gel-free interlocking armored cables are flame-retardant, indoor/outdoor, plenum-rated cables for interbuilding and intrabuilding backbones in aerial, duct and riser applications. Encased in a spirally wrapped, aluminum interlocking armor for ruggedness and superior crush resistance, these cables are ideal for industrial and heavy traffic areas and installations requiring extra protection for optical cables and for high-fiber-count trunking applications in areas with limited conduit or vault space. The plenum rating precludes the need for a transition splice when entering the building.

These cables are available in fiber counts up to 72 fibers and are protected against water penetration by innovative waterblocking materials. These materials swell to absorb water without the use of messy gels to provide more efficient and craft-friendly cable preparation, making cable access easier and simplifies the use of buffer tube fan-out kits. The buffer tubes and fibers in each tube are color coded for quick, easy identification. The SZ-stranded, loose tube design isolates fibers from installation, environmental rigors and allows for easy midspan access. Available in 50 μm , 62.5 μm , single-mode and hybrid, the cable design is National Electrical Code[®] (NEC[®]) listed.

The armored design allows for easy one-step installation which reduces overall installation costs. The UV-resistant, flame-retardant jacket is rugged and easy to strip.

Features and Benefits

Gel-free waterblocking technology

Craft-friendly cable preparation

Loose tube design

Mechanical ruggedness and environmental durability

Color-coded tubes and fibers


Quick and easy identification

Flexible interlocking armor

Up to seven times the crush protection compared to non-armored cables

Common installations

Outdoor aerial and duct; indoor vertical riser and general purpose horizontal according to NEC Article 770



FREEDM[®] Loose Tube, Gel-Free, Interlocking Armored Cable, Plenum

12 F, 50 μ m multimode (OM2)

CORNING

Standards

Listings	National Electrical Code [®] (NEC [®]) OFNP
Design and Test Criteria	ANSI/ICEA S-104-696, CSA FT-6

Specifications

General Specifications	
Environment	Indoor/Outdoor Cables
Application	Aerial, Direct Buried, Duct, General Purpose Horizontal, (Vertical Riser)
Cable Type	Loose Tube
Product Type	Interlocking armor
Flame Rating	Plenum (OFCP)
Fiber Category	50 μ m MM (OM2)

Temperature Range	
Storage	-40 °C to 70 °C (-40 °F to 158 °F)
Installation	0 °C to 60 °C (32 °F to 140 °F)
Operation	-40 °C to 70 °C (-40 °F to 158 °F)

Cable Design	
Central Element	Dielectric
Fiber Count	12
Fiber Coloring	Blue, Orange, Green, Brown, Slate, White, Red, Black, Yellow, Violet, Rose, Aqua
Fibers per Tube	12
Number of Tube Positions	6
Number of Active Tubes	1
Buffer Tube Color Coding	Blue
Buffer Tube Diameter	3.0 mm (0.12 in)
Number of Filling Elements	5
Tape	Water-swellable
Number of Ripcords	2
Inner Jacket Material	Flame-Retardant, UV-Resistant

FREEDM® Loose Tube, Gel-Free, Interlocking Armored Cable, Plenum

12 F, 50 µm multimode (OM2)

CORNING

Cable Design

Tensile Strength Elements and/or Armoring - Layer 1	Interlocking armor
Outer Jacket Material	Flame-Retardant, UV-Resistant
Outer Jacket Color	Black

Mechanical Characteristics Cable

Min. Bend Radius Installation	299 mm (11.8 in)
Min. Bend Radius Operation	199 mm (7.8 in)
Max. Tensile Strength, Short-Term	1350 N (300 lbf)
Max. Tensile Strength, Long-Term	400 N (90 lbf)
Weight	192.4 kg/km (129.3 lb/1000 ft)
Nominal Inner Cable Diameter	7.4 mm (0.29 in)
Nominal Outer Diameter	14.3 mm (0.56 in)

Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2002/95/EG
------	---

Fiber Specifications

Optical Characteristics (cabled)

Fiber Core Diameter	50 µm
Fiber Category	OM2
Fiber Code	T
Performance Option Code	31
Wavelengths	850 nm / 1300 nm
Maximum Attenuation	3.0 dB/km / 1.0 dB/km
Serial 1 Gigabit Ethernet	750 m / 500 m
Serial 10 Gigabit Ethernet	150 m / -
Min. Overfilled Launch (OFL) Bandwidth	700 MHz*km / 500 MHz*km
Minimum Effective Modal Bandwidth (EMB)	950 MHz*km / -

- Notes: 1) 50 µm multimode fiber macrobend loss ≤ 0.2 dB at 850 nm for two turns around 7.5 mm radius mandrel.
2) Improved attenuation and bandwidth options available.
3) Bend-insensitive single-mode fibers available on request.
4) Contact a Corning Customer Care Representative for additional information.

FREEDM® Loose Tube, Gel-Free, Interlocking Armored Cable, Plenum

12 F, 50 µm multimode (OM2)



Ordering Information

Part Number	012TSP-T4131DA3
Product Description	FREEDM® Loose Tube, Gel-Free, Interlocking Armored Cable, Plenum, 12 F, 50 µm multimode (OM2)
EAN Code	4056418176093



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks.

All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2016 Corning Optical Communications. All rights reserved.