

FREEDM® LST™ Loose Tube, Gel-Free, Interlocking Armored Cable, Riser

12 F, SMF-28® Ultra fiber, Single-mode (OS2)


CORNING

Corning FREEDM® LST™ gel-free interlocking armored cables are flame-retardant, indoor/outdoor, riser-rated cables designed for interbuilding and intrabuilding backbones in aerial, duct and riser applications. Encased in a spirally wrapped, aluminum interlocking armor for ruggedness and superior crush resistance, these cables are ideal for industrial and heavy traffic areas and installations requiring extra protection for optical cables and for high-fiber-count trunking applications in areas with limited conduit or vault space. The riser rating precludes the need for a transition splice when entering the building.

These cables are protected against water penetration by innovative waterblocking tapes and yarns that swell to absorb water without the use of messy gels to provide more efficient and craft-friendly cable preparation. This waterblocking technology makes cable access easier and simplifies the use of buffer tube fan-out kits. The buffer tubes and fibers in each tube are color coded for quick, easy identification. The SZ-stranded, loose tube design isolates fibers from installation, environmental rigors and allows for easy mid-span access.

The cable design is also National Electrical Code® (NEC®) listed (OFCR and FT-4) and meets NEC Article 770. The flexible, interlocking armored design offers over seven times the crush protection compared to unarmored cables (as characterized to ICEA-696) and allows easy one-step installation, thereby reducing the overall installation costs. The UV-resistant, flame-retardant jacket is rugged, durable and easy to strip.

Note: This cable is available in 12 different jacket colors – blue, orange, green, brown, slate, white, red, black, yellow, violet, rose and aqua. The colored jacket allows for easy visual identification of the cables while still providing all of the required environmental protection of an indoor/outdoor cable jacket. Black is the standard jacket color using the part numbers shown here. Contact Customer Care at 1-800-743-2675 to order other color options.



Features and Benefits

Flexible, interlocking armor design

Six times crush protection

Gel-free waterblocking technology

Craft-friendly cable preparation

Color-coded tubes and fibers

Quick and easy identification

UV-resistant, flame-retardant jacket

Rugged, durable and easy to strip

CORNING

FREEDM[®] LST[™] Loose Tube, Gel-Free, Interlocking Armored Cable, Riser

12 F, SMF-28[®] Ultra fiber, Single-mode (OS2)

CORNING

Standards

Approvals and Listings	National Electrical Code [®] (NEC [®]) OFCR, CSA OFC FT-4
Common Installations	Outdoor aerial and duct; indoor vertical riser and general purpose horizontal according to NEC Article 770
Design and Test Criteria	ANSI/ICEA S-104-696

Specifications

General Specifications	
Environment	Indoor/Outdoor
Application	Aerial, Direct Buried, Duct, General Purpose Horizontal, (Vertical Riser)
Cable Type	Loose Tube
Product Type	Interlocking Armor
Flame Rating	Riser (OFCR)
Fiber Category	SMF-28 [®] Ultra fiber

Temperature Range	
Storage	-40 °C to 70 °C (-40 °F to 158 °F)
Installation	-10 °C to 60 °C (14 °F to 140 °F)
Operation	-40 °C to 70 °C (-40 °F to 158 °F)

Cable Design	
Fiber Count	12
Fiber Coloring	Blue, Orange, Green, Brown, Slate, White, Red, Black, Yellow, Violet, Rose, Aqua
Fibers per Tube	12
Number of Tube Positions	1
Number of Active Tubes	1
Tensile Strength Elements and/or Armoring - Layer 1	Water-swellable dielectric strength members
Number of Ripcords	1
Inner Jacket Material	Flame-Retardant, UV-Resistant

FREEDM[®] LST[™] Loose Tube, Gel-Free, Interlocking Armored Cable, Riser

12 F, SMF-28[®] Ultra fiber, Single-mode (OS2)

CORNING

Cable Design

Tensile Strength Elements and/or Armoring - Layer 2	Interlocking Armor
Outer Jacket Material	Flame-Retardant, UV-Resistant
Outer Jacket Color	Black

Mechanical Characteristics Cable

Max. Tensile Strength, Short-Term	1350 N (300 lbf)
Max. Tensile Strength, Long-Term	400 N (90 lbf)
Nominal Core Diameter	8.0 mm (0.31 in)
Nominal Outer Diameter	13.7 mm (0.54 in)
Min. Bend Radius Installation	205 mm (8.1 in)
Min. Bend Radius Operation	137 mm (5.4 in)
Weight	146 kg/km (98 lb/1000 ft)

Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

Fiber Specifications

Optical Characteristics (cabled)

Fiber Name	SMF-28 [®] Ultra fiber
Fiber Category	ITU-TG.657.A1
Fiber Code	Z
Performance Option Code	01
Wavelengths	1310 nm / 1383 nm / 1550 nm
Maximum Attenuation	0.4 dB/km / 0.4 dB/km / 0.3 dB/km
Typical Attenuation	0.33 dB/km / 0.33 dB/km / 0.19 dB/km

* For more information on typical attenuation please see the Corning whitepaper at http://csmedia.corning.com/opcomm//Resource_Documents/whitepapers_rl/LAN-1863-AEN.pdf

FREEDM® LST™ Loose Tube, Gel-Free, Interlocking Armored Cable, Riser

12 F, SMF-28® Ultra fiber, Single-mode (OS2)



Ordering Information

Part Number	012ZSF-T4101DA1
Product Description	FREEDM® LST™ Single-Tube, Gel-Free, Interlocking Armored Cable, Riser, 12 F, SMF-28® Ultra fiber, Single-mode (OS2)



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks.

All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2017 Corning Optical Communications. All rights reserved.