


Fan-Out Tight-Buffered Cable, Riser

16 F, 2.9 mm Subunits, 50 μ m multimode (OM4)

CORNING

Corning fan-out riser cables are designed for use in building backbone and horizontal cabling. These multifiber cables use individually jacketed 900 μ m TBII Buffered Fibers enabling easy, consistent stripping and facilitating termination. The fibers are stranded around a dielectric central member with a flame-retardant outer jacket, making this cable particularly useful for applications requiring direct connection to terminal equipment or requiring extra rugged cables.

This cable is available in 12 different jacket colors – blue, orange, green, brown, slate, white, red, black, yellow, violet, rose and aqua. The colored jacket allows for easy visual identification of the cables. The standard jacket color will be determined by the dominant fiber type in the cable and will use the standard part numbers shown here. Contact Customer Care at 1-800-743-2675 to order other color options.



Features and Benefits

900 μ m Buffered Fibers

Easy, consistent stripping

Flame-retardant jacket

Rugged and durable

All-dielectric construction

Requires no grounding or bonding


Standards

Approvals and Listings

National Electrical Code® (NEC®) OFNR, CSA FT-4, ICEA S-83-596

Flame Resistance

UL-1666 (for riser and general building applications)



Specifications

General Specifications

Environment	Indoor
Application	General Purpose Horizontal, Vertical Riser
Cable Type	Tight-Buffered
Product Type	Distribution

CORNING

Fan-Out Tight-Buffered Cable, Riser

16 F, 2.9 mm Subunits, 50 μ m multimode (OM4)

CORNING

General Specifications

Flame Rating	Riser (OFNR)
Fiber Category	50 μ m MM (OM4)

Temperature Range

Storage	-40 °C to 70 °C (-40 °F to 158 °F)
Installation	-10 °C to 60 °C (14 °F to 140 °F)
Operation	-20 °C to 70 °C (-4 °F to 158 °F)

Cable Design

Central Element	GRP
Fiber Count	16
Tight Buffer Color	White
Tensile Strength Elements and/or Armoring - Layer 1	Dielectric strength members
Subunit Jacket Material	Flame-retardant
Subunit Color	Aqua
Subunit Diameter	2.9 mm
Number of Subunits Layer 1	5
Tensile Strength Elements and/or Armoring - Layer 2	Dielectric strength members
Number of Subunits Layer 2	11
Tensile Strength Elements and/or Armoring - Layer 3	Dielectric strength members
Number of Ripcords	1
Outer Jacket Material	Flame-retardant
Outer Jacket Color	Aqua

Mechanical Characteristics Cable

Weight	186 kg/km (125 lb/1000 ft)
Nominal Outer Diameter	15.5 mm (0.6 in)
Max. Tensile Strength, Short-Term	1320 N (300 lbf)
Max. Tensile Strength, Long-Term	400 N (90 lbf)
Min. Bend Radius Installation	233 mm (9.2 in)
Min. Bend Radius Operation	155 mm (6.1 in)

Fan-Out Tight-Buffered Cable, Riser

16 F, 2.9 mm Subunits, 50 µm multimode (OM4)

CORNING

Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

Fiber Specifications

Optical Characteristics (cabled)

Fiber Core Diameter	50 µm
Fiber Category	OM4
Fiber Code	T
Performance Option Code	90
Wavelengths	850 nm / 1300 nm
Maximum Attenuation	2.8 dB/km / 1.0 dB/km
Serial 1 Gigabit Ethernet	1000 m / 600 m
Serial 10 Gigabit Ethernet	550 m / -
Min. Overfilled Launch (OFL) Bandwidth	3500 MHz*km / 500 MHz*km
Minimum Effective Modal Bandwidth (EMB)	4700 MHz*km / -

Ordering Information

Part Number	016T61-31190-24
Product Description	Fan-Out Tight-Buffered Cable, Riser, 16 F, 2.9 mm Subunits, 50 µm multimode (OM4)



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2016 Corning Optical Communications. All rights reserved.

CORNING