

# Fan-Out Tight-Buffered Cable, Riser

16 F, 2.9 mm Subunits, 50  $\mu$ m multimode, extended 10G distance (OM4)

CORNING

Corning fan-out riser cables are designed for use in building backbone and horizontal cabling. These multifiber cables use individually jacketed 900  $\mu$ m TBII Buffered Fibers enabling easy, consistent stripping and facilitating termination. The fibers are stranded around a dielectric central member with a flame-retardant outer jacket, making this cable particularly useful for applications requiring direct connection to terminal equipment or requiring extra rugged cables.

*This cable is available in 12 different jacket colors – blue, orange, green, brown, slate, white, red, black, yellow, violet, rose and aqua. The colored jacket allows for easy visual identification of the cables. The standard jacket color will be determined by the dominant fiber type in the cable and will use the standard part numbers shown here. Contact Customer Care at 1-800-743-2675 to order other color options.*

## Features and Benefits

### 900 $\mu$ m Buffered Fibers

Easy, consistent stripping

### Flame-retardant jacket

Rugged and durable

### All-dielectric construction

Requires no grounding or bonding


## Standards

### Approvals and Listings


National Electrical Code® (NEC®) OFNR, CSA FT-4, ICEA S-83-596

### Flame Resistance

UL-1666 (for riser and general building applications)



Part Number: 016T61-31191-24



Cross Section of Part Number: 016T61-31191-24

# Fan-Out Tight-Buffered Cable, Riser

16 F, 2.9 mm Subunits, 50  $\mu$ m multimode, extended 10G distance (OM4)

CORNING

## Specifications

| General Specifications |  |
|------------------------|--|
| Environment            | Indoor                                     |
| Application            | General Purpose Horizontal, Vertical Riser |
| Cable Type             | Tight-Buffered                             |
| Product Type           | Distribution                               |
| Flame Rating           | Riser (OFNR)                               |
| Fiber Category         | 50 $\mu$ m MM (OM4+)                       |

| Temperature Range |                                    |
|-------------------|------------------------------------|
| Storage           | -40 °C to 70 °C (-40 °F to 158 °F) |
| Installation      | -10 °C to 60 °C (14 °F to 140 °F)  |
| Operation         | -20 °C to 70 °C (-4 °F to 158 °F)  |

| Cable Design  |                             |
|---|-----------------------------|
| Central Element                                     | GRP                         |
| Fiber Count   | 16                          |
| Tight Buffer Color                                  | White                       |
| Tensile Strength Elements and/or Armoring - Layer 1 | Dielectric strength members |
| Subunit Jacket Material                             | Flame-retardant             |
| Subunit Color                                       | Aqua                        |
| Subunit Diameter                                    | 2.9 mm                      |
| Number of Subunits Layer 1                          | 5                           |
| Tensile Strength Elements and/or Armoring - Layer 2 | Dielectric strength members |
| Number of Subunits Layer 2                          | 11                          |
| Tensile Strength Elements and/or Armoring - Layer 3 | Dielectric strength members |
| Number of Ripcords                                  | 1                           |
| Outer Jacket Material                               | Flame-retardant             |
| Outer Jacket Color                                  | Aqua                        |

| Mechanical Characteristics Cable  |                            |
|-----------------------------------|----------------------------|
| Weight                            | 186 kg/km (125 lb/1000 ft) |
| Nominal Outer Diameter            | 15.5 mm (0.6 in)           |
| Max. Tensile Strength, Short-Term | 1320 N (300 lbf)           |

# Fan-Out Tight-Buffered Cable, Riser

16 F, 2.9 mm Subunits, 50 µm multimode, extended 10G distance (OM4)

CORNING

## Mechanical Characteristics Cable

|                                  |                 |
|----------------------------------|-----------------|
| Max. Tensile Strength, Long-Term | 400 N (90 lbf)  |
| Min. Bend Radius Installation    | 233 mm (9.2 in) |
| Min. Bend Radius Operation       | 155 mm (6.1 in) |

## Chemical Characteristics

|      |   |
|------|---|
| RoHS | Free of hazardous substances according to RoHS 2011/65/EU |
|------|---|

## Fiber Specifications

### Optical Characteristics (cabled)

|   |                          |
|---|--------------------------|
| Fiber Core Diameter                     | 50 µm                    |
| Fiber Category                          | OM4 Extended Distance    |
| Fiber Code                              | T                        |
| Performance Option Code                 | 91                       |
| Wavelengths                             | 850 nm / 1300 nm         |
| Maximum Attenuation                     | 2.8 dB/km / 1.0 dB/km    |
| Serial 1 Gigabit Ethernet               | 1100 m / 600 m           |
| Serial 10 Gigabit Ethernet              | 600 m / -                |
| Min. Overfilled Launch (OFL) Bandwidth  | 3500 MHz*km / 500 MHz*km |
| Minimum Effective Modal Bandwidth (EMB) | 5350 MHz*km / -          |

## Ordering Information

|                     |  |
|---------------------|--|
| Part Number         | 016T61-31191-24  |
| Product Description | Fan-Out Tight-Buffered Cable, Riser, 16 F, 2.9 mm Subunits, 50 µm multimode, extended 10G distance (OM4) |



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • [www.corning.com/opcomm](http://www.corning.com/opcomm)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/trademarks](http://www.corning.com/opcomm/trademarks). All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2016 Corning Optical Communications. All rights reserved.

CORNING