

ActiFi™ FREEDM® DAS Cables for Indoor/ Outdoor Riser

24 F, 6 Cu Conductor, 16AWG

CORNING

Corning ActiFi™ FREEDM® Cables provide the ultimate solution for indoor-outdoor remote powering of distributed antenna systems (DAS). The designs use 6-, 12- or 24-fiber cables with 2, 4, 6 or 12 copper conductors. The gauge of wire (14 or 16 AWG) necessary to power the remote active gear determines distance traveled and strength required.

Corning ActiFi™ FREEDM® Cables provide a time and cost-saving solution for installations requiring remotely-powered equipment. By integrating copper and fiber in one cable, ActiFi FREEDM Cables eliminate the need to install separate power and fiber cables. This saves installation time, labor costs and duct or tray space. The compact and versatile design is available in riser or interlocking armored riser for additional protection where conduit may not be feasible.

Features and Benefits

14 or 16 AWG copper conductor

Power transmission with flexibility in design

4-, 6-, 12- or 24-fibers

Readily identifiable

Individual fibers

Easily accessible for splicing

ClearCurve® ZBL or SMF-28® Ultra fibers

Reliable performance in challenging routes

2-in-1 cable design



One cable meets power and signal needs

Standards

Approvals and Listings Fibers compliant with ITU-T G.652.D and G.657.B3

Common Installations Compliant with ICEA S-83-596 (compliant at tensile loads listed in the specifications table)

Design and Test Criteria Compliant with UL-13 and NEC 725 Class 2 (CL2P)



ActiFi™ FREEDM® DAS Cables for Indoor/ Outdoor Riser

24 F, 6 Cu Conductor, 16AWG

CORNING

Specifications

General Specifications

Environment	Indoor/Outdoor Cables
Application	Vertical Riser
Cable Type	Loose Tube
Fiber Category	ClearCurve® Single-mode ZBL

Temperature Range

Storage	-40 °C to 70 °C (-40 °F to 158 °F)
Installation	0 °C to 60 °C (14 °F to 140 °F)
Operation	-20 °C to 70 °C (-4 °F to 158 °F)

Cable Design

Central Element	Jacketed GRP
Fiber Count	24
Fiber Coloring	Blue, Orange, Green, Brown, Slate, White, Red, Black, Yellow, Violet, Rose, Aqua
Fibers per Tube	12
Number of Tube Positions	2
Number of Active Tubes	2
Buffer Tube Color Coding	Yellow
Buffer Tube Diameter	1.6 mm (0.06 in)
Number of Ripcords	1
Outer Jacket Material	Flame-retardant
Outer Jacket Color	Black

Mechanical Characteristics Cable

Max. Tensile Strength, Short-Term	2700 N (600 lbf)
Max. Tensile Strength, Long-Term	810 N (180 lbf)
Weight	137 kg/km (92 lb/1000 ft)
Nominal Outer Diameter	9.4 mm (0.37 in)
Min. Bend Radius Installation	141 mm (5.55 in)
Min. Bend Radius Operation	94 mm (3.70 in)
Conductor Size	16AWG
Number of Conductors	6

ActiFi™ FREEDM® DAS Cables for Indoor/ Outdoor Riser

24 F, 6 Cu Conductor, 16AWG



Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2002/95/EG
------	---

Fiber Specifications

Optical Characteristics (cabled)

Fiber Name	ClearCurve® ZBL
Fiber Category	G.657.B3/G.652.D
Fiber Code	U
Performance Option Code	01
Wavelengths	1310 nm / 1383 nm / 1550 nm
Maximum Attenuation	0.4 dB/km / 0.4 dB/km / 0.3 dB/km
Typical Attenuation*	0.35 dB/km / 0.35 dB/km / 0.20 dB/km

* For more information on typical attenuation please see the Corning whitepaper at http://csmedia.corning.com/opcomm//Resource_Documents/whitepapers_rl/LAN-1863-AEN.pdf

Ordering Information

Part Number	024UTF-61H01M20
Product Description	ActiFi™ FREEDM® DAS Cables for Indoor/Outdoor Riser, 24 F, 6 Cu Conductor, 16AWG



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2015 Corning Optical Communications. All rights reserved.

