


# Ruggedized Ribbon Cable, Plenum

36 F, Single-mode (OS2)

CORNING

Corning ruggedized ribbon plenum cables are designed for intrabuilding backbones in plenum, riser and general-purpose installation. With a flame-retardant outer jacket that meets the requirements of the National Electrical Code® (NEC®), Article 770-51(A) and NFPA 262 flame tests, the cables are also ideal for data centers and segregating secure traffic on protected distribution systems (PDS). The cables consist of fibers organized into easily identifiable 12-fiber ruggedized ribbons inside a central tube with readily identifiable ribbon ID numbers and fiber colors which allow easy access of individual fibers. Dielectric strength members provide tensile strength. These cables are compatible with standard ribbon cable procedures and hardware.

*This cable is available in 12 different jacket colors – blue, orange, green, brown, slate, white, red, black, yellow, violet, rose and aqua. The colored jacket allows for easy visual identification of the cables. The standard jacket color will be determined by the dominant fiber type in the cable and will use the standard part numbers shown here. Contact Customer Care at 1-800-743-2675 to order other color options.*



## Features and Benefits

### Precise fiber and ribbon geometries

Excellent mass splicing yields

### Ribbon ID numbers and fiber colors


Easily identifiable

### Dielectric strength members

Additional mechanical durability

### Common installations

Indoor plenum, riser and general building applications



## Standards

<b>Listings</b>	National Electrical Code® (NEC®) OFNP
<b>Design Criteria</b>	CSA FT-6
<b>Test Criteria</b>	ANSI/ICEA S-83-596

CORNING

# Ruggedized Ribbon Cable, Plenum

36 F, Single-mode (OS2)

CORNING

## Specifications

General Specifications	
Environment	Indoor
Application	General Purpose Horizontal, Vertical Riser, Plenum
Cable Type	Ribbon
Product Type	Distribution
Flame Rating	Plenum (OFNP)
Fiber Category	Single-mode (OS2)

Temperature Range	
Storage	-40 °C to 70 °C (-40 °F to 158 °F)
Installation	0 °C to 60 °C (32 °F to 140 °F)
Operation	0 °C to 70 °C (32 °F to 158 °F)

Cable Design	
Fiber Count	36
Ribbons per Tube	3
Fibers per Ribbon	12
Fiber Coloring	Blue, Orange, Green, Brown, Slate, White, Red, Black, Yellow, Violet, Rose, Aqua
Ribbon jacket material	Flame-retardant
Ribbon jacket color	Yellow
Buffer Tube Color	Natural
Buffer Tube Diameter	8.1 mm (0.32 in)
Tape	Water-swellable
Tensile Strength Elements and/or Armoring - Layer 1	Dielectric strength members
Number of Ripcords	2
Outer Jacket Material	Flame-retardant
Outer Jacket Color	Yellow

Mechanical Characteristics Cable	
Max. Tensile Strength, Short-Term	1320 N (300 lbf)
Max. Tensile Strength, Long-Term	400 N (90 lbf)
Weight	195 kg/km (131 lb/1000 ft)
Nominal Outer Diameter	13.6 mm (0.5 in)

# Ruggedized Ribbon Cable, Plenum

36 F, Single-mode (OS2)

CORNING

## Mechanical Characteristics Cable

Min. Bend Radius Installation	204 mm (8 in)
Min. Bend Radius Operation	136 mm (5.4 in)

## Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

## Fiber Specifications

### Optical Characteristics (cabled)

Fiber Name	Single-mode (OS2)
Fiber Category	G.652.D
Fiber Code	E
Performance Option Code	01
Wavelengths	1310 nm / 1383 nm / 1550 nm
Maximum Attenuation	0.4 dB/km / 0.4 dB/km / 0.3 dB/km

## Ordering Information

Part Number	036EC8-94101-20
Product Description	Ruggedized Ribbon Cable, Plenum, 36 F, Single-mode (OS2)
EAN Code	4056418164465



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • [www.corning.com/opcomm](http://www.corning.com/opcomm)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/trademarks](http://www.corning.com/opcomm/trademarks). All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2016 Corning Optical Communications. All rights reserved.

CORNING