

# ALTOS® Loose Tube, Gel-Filled, Double-Jacket Cable

36 F, Single-mode (OS2)

CORNING

Corning ALTOS® double-jacket dielectric cables are designed for duct and aerial (lashed) installation. The double-jacket construction adds a layer of protection for harsh environments. The loose tube cable design provides stable performance over a wide temperature range and is compatible with any telecommunications-grade optical fiber.

## Features and Benefits

### Two jacket layers

Provides extra protection in harsh environments

### Flexible, craft-friendly buffer tubes

Facilitate easy routing in closures

### Innovative waterblocking design

Provides efficient and craft-friendly cable preparation

### Medium-density polyethylene jacket

Rugged, durable and easy to strip (while providing superior protection against UV radiation, fungus, abrasion and other environmental factors)

### Exceeds the RDUP requirements for mid-span buffer tube slack storage

Provides flexibility for mid-span access applications



## Standards

### Approvals and Listings

USDA Rural Development Programs

### Design and Test Criteria

Telcordia GR-20, ICEA-640



# ALTOS® Loose Tube, Gel-Filled, Double-Jacket Cable

36 F, Single-mode (OS2)

CORNING

## Specifications

### General Specifications

Environment	Outdoor
Application	Aerial, Duct
Cable Type	Loose Tube
Product Type	Dielectric
Fiber Category	Single-mode (OS2)

### Temperature Range

Storage	-40 °C to 70 °C (-40 °F to 158 °F)
Installation	-30 °C to 70 °C (-22 °F to 158 °F)
Operation	-40 °C to 70 °C (-40 °F to 158 °F)

### Cable Design

Central Element	Dielectric
Fiber Count	36
Fiber Coloring	Blue, Orange, Green, Brown, Slate, White, Red, Black, Yellow, Violet, Rose, Aqua
Fibers per Tube	12
Number of Tube Positions	6
Number of Active Tubes	3
Buffer Tube Color Coding, Layer 1	Blue, Orange, Green
Buffer Tube Diameter	2.5 mm (0.1 in)
Number of Filling Elements	3
Tape	Water-swellaable
Inner Jacket Material	Polyethylene (PE)
Tape, Layer 3	Water-swellaable
Number of Ripcords	1
Tensile Strength Elements and/or Armoring - Layer 1	Dielectric strength members
Outer Jacket Material	Polyethylene (PE)
Outer Jacket Color	Black
Maximum Fibers per Tube	12

CORNING

# ALTOS® Loose Tube, Gel-Filled, Double-Jacket Cable

36 F, Single-mode (OS2)

CORNING

## Mechanical Characteristics Cable

Max. Tensile Strength, Short-Term	2700 N (600 lbf)
Max. Tensile Strength, Long-Term	890 N (200 lbf)
Weight	114 kg/km (76 lb/1000 ft)
Nominal Outer Diameter	12.5 mm (0.49 in)
Min. Bend Radius Installation	188 mm (7.4 in)
Min. Bend Radius Operation	125 mm (4.9 in)

## Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

## Fiber Specifications

### Optical Characteristics (cabled)

Fiber Name	Single-mode (OS2)
Fiber Category	G.652.D
Fiber Code	E
Performance Option Code	01
Wavelengths	1310 nm / 1383 nm / 1550 nm
Maximum Attenuation	0.4 dB/km / 0.4 dB/km / 0.3 dB/km

## Ordering Information

Part Number	036EUE-T4101A20
Product Description	ALTOS® Loose Tube, Gel-Filled, Double-Jacket Cable, 36 F, Single-mode (OS2)
EAN Code	4056418160542



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • [www.corning.com/opcomm](http://www.corning.com/opcomm)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/trademarks](http://www.corning.com/opcomm/trademarks). All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2016 Corning Optical Communications. All rights reserved.

CORNING