

# Industrial LSZH™ Tray-Rated, Loose Tube, Gel-Free Cable

36 F, 62.5 μm multimode (OM1)

CORNING



Corning Industrial LSZH™ fiber optic cables are designed for industrial building backbones and harsh environments atypical of traditional datacom systems. Based on proven stranded loose tube cable designs, these industrial cables are flame-retardant and have been tested to meet mechanical/environmental conditions exceeding the requirements set for traditional datacom cables. The 250 μm color-coded individual fibers offer quick and easy identification during installation.

Corning Industrial LSZH™ cables provide life-safety benefits for industrial applications through the cables' construction. Many traditional data communication cables contain halogens in the jacket compound, which pose little risk in the controlled and protected environment of typical building air spaces, such as behind walls, under floors and in conduit. However, cables deployed in industrial applications, particularly on the plant floor, are typically exposed to greater risk of fire, extreme temperatures or chemical exposure. This often makes halogen cables inappropriate for industrial environments.

Corning Industrial LSZH™ cables eliminate these risks in the event of a fire in the industrial environment. In addition, the LSZH compound does not drip when superheated; the material burns to ash, eliminating the onset of secondary fires.

When cables containing halogens ignite, they emit highly reactive gases that can be harmful if inhaled. When halogens combine with water, acids are formed. These acids damage both living tissue and inorganic materials, such as metal and electronic equipment. Corning industrial LSZH cables eliminate these risks in the event of a fire in the industrial environment. In addition, the LSZH compound does not drip when superheated; the material burns to ash, eliminating the onset of secondary fires.

*Note: This cable is available in 12 different jacket colors – blue, orange, green, brown, slate, white, red, black, yellow, violet, rose and aqua. The colored jacket allows for easy visual identification of the cables while still providing all of the required environmental protection of an indoor/outdoor cable jacket. Black is the standard jacket color using the part numbers shown here. Contact Customer Care at 1-800-743-2675 to order other color options.*



## Features and Benefits

**Low-smoke, zero-halogen sheath**  
Key life-safety benefit

**Meets cyclic impact and chemical resistance test**  
Superior performance

# Industrial LSZH™ Tray-Rated, Loose Tube, Gel-Free Cable

36 F, 62.5 µm multimode (OM1)



## Features and Benefits

### Common installations

Outdoor aerial and duct; indoor general purpose horizontal according to NEC Article 770

## Standards

### Listings

National Electrical Code® (NEC®) OFN-LS, Sunlight Resistant (SUN RES); IEEE-383/IEEE-1202 flame test; Suitable for Direct Burial (DIR BUR); IEC 60332-3, IEC 60754-2, IEC 61034; MSHA 30 CFR Part 7-K, Section 7.408

### Design and Test Criteria

ANSI/ICEA S-104-696; UL 13; UL 444; UL 1277; UL 1685; CSA C22.2 No. 230 and No. 232; CSA OFC (FT-4-S1)

## Specifications

| General Specifications |   |
|------------------------|---|
| Environment            | Indoor/Outdoor Cables   |
| Application            | Aerial, Direct Buried, Duct, Tray Rated, (General Purpose Horizontal) |
| Cable Type             | Loose Tube  |
| Product Type           | Dielectric  |
| Flame Rating           | LSZH™ (OFN-LS)  |
| Fiber Category         | 62.5 µm MM (OM1)  |

| Temperature Range |                                    |
|-------------------|------------------------------------|
| Storage           | -40 °C to 70 °C (-40 °F to 158 °F) |
| Installation      | -30 °C to 60 °C (-22 °F to 140 °F) |
| Operation         | -40 °C to 70 °C (-40 °F to 158 °F) |

# Industrial LSZH™ Tray-Rated, Loose Tube, Gel-Free Cable

36 F, 62.5 µm multimode (OM1)

CORNING

## Cable Design

|                            |  |
|----------------------------|--|
| Central Element            | Dielectric   |
| Fiber Count                | 36   |
| Fiber Coloring             | Blue, Orange, Green, Brown, Slate, White, Red, Black, Yellow, Violet, Rose, Aqua |
| Fibers per Tube            | 12   |
| Number of Tube Positions   | 6  |
| Number of Active Tubes     | 3  |
| Buffer Tube Color Coding   | Blue, Orange, Green  |
| Buffer Tube Diameter       | 2.5 mm (0.1 in)  |
| Number of Filling Elements | 3  |
| Tape                       | Water-swellable  |
| Tape, Layer 2              | Flame-retardant tape   |
| Tape, Layer 3              | Water-swellable  |
| Number of Ripcords         | 2  |
| Outer Jacket Material      | Flame-retardant, non-corrosive/low-smoke, zero-halogen (FRNC/LSZH) material      |
| Outer Jacket Color         | Black  |

## Mechanical Characteristics Cable

|                                   |                            |
|-----------------------------------|----------------------------|
| Max. Tensile Strength, Short-Term | 2700 N (600 lbf)           |
| Max. Tensile Strength, Long-Term  | 810 N (180 lbf)            |
| Weight                            | 152 kg/km (102 lb/1000 ft) |
| Nominal Outer Diameter            | 12.8 mm (0.50 in)          |
| Min. Bend Radius Installation     | 192 mm (7.6 in)            |
| Min. Bend Radius Operation        | 128 mm (5.0 in)            |

## Chemical Characteristics

|      |   |
|------|---|
| RoHS | Free of hazardous substances according to RoHS 2011/65/EU |
|------|---|

# Industrial LSZH™ Tray-Rated, Loose Tube, Gel-Free Cable

36 F, 62.5 µm multimode (OM1)



## Fiber Specifications

| Optical Characteristics (cabled)        |                         |
|---|-------------------------|
| Fiber Core Diameter                     | 62.5 µm                 |
| Fiber Category                          | OM1                     |
| Fiber Code                              | K                       |
| Performance Option Code                 | 30                      |
| Wavelengths                             | 850 nm / 1300 nm        |
| Maximum Attenuation                     | 3.4 dB/km / 1.0 dB/km   |
| Serial 1 Gigabit Ethernet               | 300 m / 550 m           |
| Serial 10 Gigabit Ethernet              | 33 m / -                |
| Min. Overfilled Launch (OFL) Bandwidth  | 200 MHz*km / 500 MHz*km |
| Minimum Effective Modal Bandwidth (EMB) | 220 MHz*km / -          |

Notes: 1) Improved attenuation and bandwidth options available.  
2) Bend-insensitive single-mode fibers available on request.  
3) Contact a Corning Customer Care Representative for additional information.

## Ordering Information

|                     |  |
|---------------------|--|
| Part Number         | 036KUZ-T4130D2N  |
| Product Description | Industrial LSZH™ Tray-Rated, Loose Tube, Gel-Free Cable, 36 F, 62.5 µm multimode (OM1) |
| EAN Code            | 4056418172088  |



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • [www.corning.com/opcomm](http://www.corning.com/opcomm)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/trademarks](http://www.corning.com/opcomm/trademarks). All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2016 Corning Optical Communications. All rights reserved.

