

MIC[®] Unitized Tight-Buffered Cable, Plenum

36 F, 50 μm multimode (OM4)

CORNING

Corning MIC[®] unitized plenum cables are designed for use in plenum, riser and general purpose environments for intrabuilding backbone installations. These multifiber cables use individually jacketed 900 μm buffered fibers enabling easy, consistent stripping and facilitating termination. The stranded subunits of 6-, 12-, or 24-fibers allow quick and easy identification and are surrounded by dielectric strength members and protected by a flame-retardant outer jacket.

The all-dielectric cable construction requires no grounding or bonding, making these cables ideal for routing inside buildings including riser shafts, to the telecommunications rooms and workstations. The MIC Unitized Riser Cables meet the application requirements of the National Electrical Code[®] (NEC[®]) Article 770 and the ICEA S-83-596 test criteria. They are OFNP and FT-6 listed.

This cable is available in 12 different jacket colors – blue, orange, green, brown, slate, white, red, black, yellow, violet, rose and aqua. The colored jacket allows for easy visual identification of the cables. The standard jacket color will be determined by the dominant fiber type in the cable and will use the standard part numbers shown here. Contact Customer Care at 1-800-743-2675 to order other color options.

Features and Benefits

900 μm Buffered Fibers

Easy, consistent stripping

6- or 12-fiber jacketed subunits

Quick and easy identification

All-dielectric construction

Requires no grounding or bonding

Flame-retardant jacket

Rugged and durable


Standards

Approvals and Listings


National Electrical Code[®] (NEC[®]) OFNP, CSA FT-6, ICEA S-83-596

Flame Resistance

NFPA 262 (for plenum, riser and general building applications)



Part Number: 036T88-61190-29



Cross Section of Part Number: 036T88-61190-29

MIC[®] Unitized Tight-Buffered Cable, Plenum

36 F, 50 µm multimode (OM4)

CORNING

Specifications

General Specifications	
Environment	Indoor
Application	General Purpose Horizontal, Vertical Riser, Plenum
Cable Type	Tight-Buffered
Product Type	Distribution
Flame Rating	Plenum (OFNP)
Fiber Category	50 µm MM (OM4)

Temperature Range	
Storage	-40 °C to 70 °C (-40 °F to 158 °F)
Installation	0 °C to 60 °C (32 °F to 140 °F)
Operation	0 °C to 70 °C (32 °F to 158 °F)

Cable Design	
Central Element	Jacketed GRP
Fiber Count	36
Number of Active Tubes	6
Subunit Color	Aqua
Number of Fibers per Subunit	6
Subunit Diameter	4.40 mm (0.17 in)
Tight buffer color subunit	Blue, Orange, Green, Brown, Slate, White
Tensile Strength Elements and/or Armoring - Layer 1	Dielectric strength members
Number of Ripcords	7
Outer Jacket Material	Flame-retardant
Outer Jacket Color	Aqua

Mechanical Characteristics Cable	
Max. Tensile Strength, Short-Term	660 N (150 lbf)
Max. Tensile Strength, Long-Term	200 N (45 lbf)
Nominal Outer Diameter	14.8 mm (0.58 in)
Weight	207.3 kg/km (147.0 lb/1000 ft)
Min. Bend Radius Installation	222 mm (8.7 in)
Min. Bend Radius Operation	148 mm (5.8 in)

MIC[®] Unitized Tight-Buffered Cable, Plenum

36 F, 50 µm multimode (OM4)

CORNING

Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

Fiber Specifications

Optical Characteristics (cabled)

Fiber Core Diameter	50 µm
Fiber Category	OM4
Fiber Code	T
Performance Option Code	90
Wavelengths	850 nm / 1300 nm
Maximum Attenuation	2.8 dB/km / 1.0 dB/km
Serial 1 Gigabit Ethernet	1000 m / 600 m
Serial 10 Gigabit Ethernet	550 m / -
Min. Overfilled Launch (OFL) Bandwidth	3500 MHz*km / 500 MHz*km
Minimum Effective Modal Bandwidth (EMB)	4700 MHz*km / -

Ordering Information

Part Number	036T88-61190-29
Product Description	MIC [®] Unitized Tight-Buffered Cable, Plenum, 36 F, 50 µm multimode (OM4)
EAN Code	4056418160283



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks.

All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2016 Corning Optical Communications. All rights reserved.

CORNING