

ALTOS® Loose Tube, Gel-Filled Cable

60 F, Single-mode (OS2)

CORNING

Corning ALTOS® all-dielectric cables are lightweight cables designed for duct and aerial (lashed) installation. The loose tube design provides stable performance over a wide temperature range and is compatible with any telecommunications-grade optical fiber.

Features and Benefits

Flexible, craft-friendly buffer tubes

Facilitate easy routing in closures

SZ-stranded, loose tube design

Isolates fibers from installation and environmental rigors and facilitates mid-span access

Dielectric central strength member

No preferential bend and requires no bonding or grounding



Medium-density polyethylene jacket

Rugged, durable and easy to strip (while providing superior protection against UV radiation, fungus, abrasion and other environmental factors)

Standards

Approvals and Listings USDA Rural Development Programs

Design and Test Criteria Telcordia GR-20, ICEA-640



ALTOS[®] Loose Tube, Gel-Filled Cable

60 F, Single-mode (OS2)

CORNING

Specifications

General Specifications

| | |
|----------------|-------------------|
| Environment | Outdoor |
| Application | Aerial, Duct |
| Cable Type | Loose Tube |
| Product Type | Dielectric |
| Fiber Category | Single-mode (OS2) |

Temperature Range

| | |
|--------------|------------------------------------|
| Storage | -40 °C to 70 °C (-40 °F to 158 °F) |
| Installation | -30 °C to 70 °C (-22 °F to 158 °F) |
| Operation | -40 °C to 70 °C (-40 °F to 158 °F) |

Cable Design

| | |
|----------------------------|----------------------------------------------------------------------------------|
| Central Element | Dielectric |
| Fiber Count | 60 |
| Fiber Coloring | Blue, Orange, Green, Brown, Slate, White, Red, Black, Yellow, Violet, Rose, Aqua |
| Fibers per Tube | 12 |
| Number of Tube Positions | 6 |
| Number of Active Tubes | 5 |
| Buffer Tube Color Coding | Blue, Orange, Green, Brown, Slate |
| Buffer Tube Diameter | 2.5 mm (0.1 in) |
| Number of Filling Elements | 1 |
| Tape | Water-swellable |
| Number of Ripcords | 1 |
| Outer Jacket Material | Polyethylene (PE) |
| Outer Jacket Color | Black |
| Maximum Fibers per Tube | 12 |

Mechanical Characteristics Cable

| | |
|-----------------------------------|--------------------------|
| Max. Tensile Strength, Short-Term | 2700 N (600 lbf) |
| Max. Tensile Strength, Long-Term | 890 N (200 lbf) |
| Weight | 80 kg/km (54 lb/1000 ft) |
| Nominal Outer Diameter | 10.5 mm (0.41 in) |

CORNING

ALTOS® Loose Tube, Gel-Filled Cable

60 F, Single-mode (OS2)

CORNING

Mechanical Characteristics Cable

| | |
|-------------------------------|-----------------|
| Min. Bend Radius Installation | 158 mm (6.2 in) |
| Min. Bend Radius Operation | 105 mm (4.1 in) |

Chemical Characteristics

| | |
|------|-----------------------------------------------------------|
| RoHS | Free of hazardous substances according to RoHS 2002/95/EG |
|------|-----------------------------------------------------------|

Fiber Specifications

Optical Characteristics (cabled)

| | |
|-------------------------|--------------------------------------|
| Fiber Name | Single-mode (OS2) |
| Fiber Category | G.652.D |
| Fiber Code | E |
| Performance Option Code | 00 |
| Wavelengths | 1310 nm / 1383 nm / 1550 nm |
| Maximum Attenuation | 0.35 dB/km / 0.35 dB/km / 0.25 dB/km |

Ordering Information

| | |
|---------------------|--------------------------------------------------------------|
| Part Number | 060EU4-T4100A20 |
| Product Description | ALTOS® Loose Tube, Gel-Filled Cable, 60 F, Single-mode (OS2) |
| EAN Code | 4056418186078 |



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2016 Corning Optical Communications. All rights reserved.

CORNING