


# MIC<sup>®</sup> Unitized Tight-Buffered, Interlocking Armored Cable, Riser

60 F, 50 μm multimode (OM2)

CORNING

Corning MIC<sup>®</sup> interlocking armored riser cables are designed for use in intrabuilding backbone and horizontal installations. They use individually jacketed 900 μm buffered fibers enabling easy, consistent stripping and facilitating termination. The fibers are grouped into 6-, 12-, or 24-fiber jacketed subunits and surrounded by a dielectric central member. The core is protected by a flexible, spirally wrapped, aluminum interlocking armor that offers easy, one-step installation and up to seven times the crush protection of unarmored cables. With a flame-retardant outer jacket, this cable is particularly useful for heavy traffic or more challenging mechanical exposure conditions and applications requiring extra rugged cables.

*This cable is available in 12 different jacket colors – blue, orange, green, brown, slate, white, red, black, yellow, violet, rose and aqua. The colored jacket allows for easy visual identification of the cables. The standard jacket color will be determined by the dominant fiber type in the cable and will use the standard part numbers shown here. Contact Customer Care at 1-800-743-2675 to order other color options.*



## Features and Benefits

### Flexible, interlocking armor design

Seven times crush protection compared to unarmored cables

### 900 μm Buffered Fibers


Easy, consistent stripping

### 6- or 12-fiber jacketed subunits

Quick and easy identification

### Flame-retardant jacket

Rugged and durable



## Standards

### Listings

National Electrical Code<sup>®</sup>  
(NEC<sup>®</sup>) OFCR, FT-4

### Design and Test Criteria

UL-1666 and CSA FT-4 (for riser and general building applications); ICEA S-83-596

# MIC<sup>®</sup> Unitized Tight-Buffered, Interlocking Armored Cable, Riser

60 F, 50 μm multimode (OM2)

CORNING

## Specifications

### General Specifications

Environment	Indoor
Application	General Purpose Horizontal, Vertical Riser
Cable Type	Tight-Buffered
Product Type	Interlocking armor
Flame Rating	Riser (OFCR)
Fiber Category	50 μm MM (OM2)

### Temperature Range

Storage	-40 °C to 70 °C (-40 °F to 158 °F)
Installation	-10 °C to 60 °C (14 °F to 140 °F)
Operation	-20 °C to 70 °C (-4 °F to 158 °F)

### Cable Design

Central Element	Jacketed GRP
Fiber Count	60
Number of Active Tubes	5
Subunit Color	Orange
Number of Fibers per Subunit	12
Subunit Diameter	5.55 mm (0.22 in)
Tight buffer color subunit	Blue, Orange, Green
Tensile Strength Elements and/or Armoring - Layer 1	Dielectric strength members
Tight Buffer Color Subunit, Layer 2	Brown, Slate, White, Red, Black, Yellow, Violet, Rose, Aqua
Number of Ripcords	7
Outer Jacket Material	Flame-retardant
Outer Jacket Color	Orange

### Mechanical Characteristics Cable

Max. Tensile Strength, Short-Term	1320 N (300 lbf)
Max. Tensile Strength, Long-Term	400 N (90 lbf)
Nominal Inner Cable Diameter	17.9 mm (0.70 in)
Nominal Outer Diameter	24.9 mm (.98 in)
Weight	421.0 kg/km (282.9 lb/1000 ft)

# MIC<sup>®</sup> Unitized Tight-Buffered, Interlocking Armored Cable, Riser

60 F, 50 µm multimode (OM2)

CORNING

## Mechanical Characteristics Cable

Min. Bend Radius Installation	374 mm (14.7 in)
Min. Bend Radius Operation	249 mm (9.8 in)

## Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

## Fiber Specifications

### Optical Characteristics (cabled)

Fiber Core Diameter	50 µm
Fiber Category	OM2
Fiber Code	T
Performance Option Code	31
Wavelengths	850 nm / 1300 nm
Maximum Attenuation	2.8 dB/km / 1.0 dB/km
Serial 1 Gigabit Ethernet	750 m / 600 m
Serial 10 Gigabit Ethernet	150 m / -
Min. Overfilled Launch (OFL) Bandwidth	700 MHz*km / 500 MHz*km
Minimum Effective Modal Bandwidth (EMB)	950 MHz*km / -

## Ordering Information

Part Number	060T81-T3131-A1
Product Description	MIC <sup>®</sup> Unitized Tight-Buffered, Interlocking Armored Cable, Riser, 60 F, 50 µm multimode (OM2)
EAN Code	4056418158785



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • [www.corning.com/opcomm](http://www.corning.com/opcomm)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/trademarks](http://www.corning.com/opcomm/trademarks). All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2016 Corning Optical Communications. All rights reserved.

CORNING