


# MIC<sup>®</sup> 250 Interlocking Armored Distribution Cable, Plenum

72 F, 62.5 μm multimode (OM1)

CORNING

Corning MIC<sup>®</sup> 250 cables utilize 250 μm color-coded optical fibers surrounded by dielectric strength members with a flexible, flame-retardant outer jacket. These cables are ideal for creating multifiber preconnectorized assemblies as the 12-fiber groupings enable efficient compatibility with multifiber connectors. The flexible, flame-retardant jacket and non-preferential bend axis allow easy installation in space-constrained areas. The core is protected by a flexible, spirally-wrapped, aluminum interlocking armor that offers easy, one-step installation.

*This cable is available in 12 different jacket colors – blue, orange, green, brown, slate, white, red, black, yellow, violet, rose and aqua. The colored jacket allows for easy visual identification of the cables. The standard jacket color will be determined by the dominant fiber type in the cable and will use the standard part numbers shown here. Contact Customer Care at 1-800-743-2675 to order other color options.*



## Features and Benefits

### Color-coded fibers

Quick and easy identification

### 12-fiber groupings

Compatibility with multifiber connectors

## Standards

### Listings


National Electrical Code<sup>®</sup>  
(NEC<sup>®</sup>) OFCP, FT-6, ICEA  
S-83-596

### Design and Test Criteria

CSA FT-6

### Flame Resistance

NFPA 262 (for plenum, riser and general building applications)



## Specifications

General Specifications	
Environment	Indoor
Application	General Purpose Horizontal, Vertical Riser, Plenum
Cable Type	Loose Tube
Product Type	Distribution

# MIC<sup>®</sup> 250 Interlocking Armored Distribution Cable, Plenum

72 F, 62.5  $\mu$ m multimode (OM1)

CORNING

## General Specifications

Flame Rating	Plenum (OFNP)
Fiber Category	62.5 $\mu$ m MM (OM1)

## Temperature Range

Storage	-40 °C to 70 °C (-40 °F to 158 °F)
Installation	0 °C to 60 °C (32 °F to 140 °F)
Operation	0 °C to 70 °C (32 °F to 158 °F)

## Cable Design

Central Element	Jacketed GRP
Fiber Count	72
Fibers per Subunit	12
Fiber Coloring	Blue, Orange, Green, Brown, Slate, White, Red, Black, Yellow, Violet, Rose, Aqua
Tensile Strength Elements and/or Armoring - Layer 1	Dielectric strength members
Subunit Jacket Material	Flame-retardant
Subunit Color	Orange
Number of Subunits	6
Number of Ripcords	1
Outer Jacket Material	Flame-retardant
Outer Jacket Color	Orange

## Mechanical Characteristics Cable

Weight	258.97 kg/km (174.01 lb/1000 ft)
Nominal Outer Diameter	17.3 mm (0.68 in)
Max. Tensile Strength, Short-Term	660 N (150 lbf)
Max. Tensile Strength, Long-Term	200 N (45 lbf)
Min. Bend Radius Installation	259.5 mm (10.2 in)
Min. Bend Radius Operation	173 mm (6.81 in)

## Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

# MIC<sup>®</sup> 250 Interlocking Armored Distribution Cable, Plenum

72 F, 62.5 μm multimode (OM1)



## Fiber Specifications

Optical Characteristics (cabled)	
Fiber Core Diameter	62.5 μm
Fiber Category	OM1
Fiber Code	K
Performance Option Code	30
Wavelengths	850 nm / 1300 nm
Maximum Attenuation	3.4 dB/km / 1.0 dB/km
Serial 1 Gigabit Ethernet	300 m / 550 m
Serial 10 Gigabit Ethernet	33 m / -
Min. Overfilled Launch (OFL) Bandwidth	200 MHz*km / 500 MHz*km
Minimum Effective Modal Bandwidth (EMB)	220 MHz*km / -

Notes: 1) Improved attenuation and bandwidth options available.  
2) Bend-insensitive single-mode fibers available on request.  
3) Contact a Corning Customer Care Representative for additional information.

## Ordering Information

Part Number	072KD8-T1330-A3
Product Description	MIC <sup>®</sup> 250 Distribution Cable, Plenum, Interlocking Armor, 72 F, 62.5 μm multimode (OM1)
EAN Code	4056418158198



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • [www.corning.com/opcomm](http://www.corning.com/opcomm)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/trademarks](http://www.corning.com/opcomm/trademarks). All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2018 Corning Optical Communications. All rights reserved.

