

# MIC® Unitized Tight-Buffered, Interlocking Armored Cable, Plenum

96 F, 50 µm multimode (OM3)

CORNING

Corning MIC® unitized interlocking armored plenum cables are standard MIC unitized cables designed for use in plenum, riser and general purpose environments for intrabuilding backbone and horizontal installations. These multifiber cables use individually jacketed 900 µm buffered fibers enabling easy, consistent stripping and facilitating termination. The fibers are grouped into 6-, 12-, or 24-fiber jacketed subunits for quick and easy identification. These subunits surround a dielectric central member and are protected by a flexible, spirally wrapped, aluminum interlocking armor that offers easy, one-step installation and up to seven times the crush protection of unarmored cables.

With a flame-retardant outer jacket, this cable is particularly useful for heavy traffic or more challenging mechanical exposure conditions and applications requiring extra rugged cables for routing inside buildings, through riser shafts, to telecommunication rooms and to workstations.

*This cable is available in 12 different jacket colors – blue, orange, green, brown, slate, white, red, black, yellow, violet, rose and aqua. The colored jacket allows for easy visual identification of the cables. The standard jacket color will be determined by the dominant fiber type in the cable and will use the standard part numbers shown here. Contact Customer Care at 1-800-743-2675 to order other color options.*

## Features and Benefits

### Flexible, interlocking armor design

Seven times crush protection compared to unarmored cables

### TBII buffered fibers

Easy, consistent stripping

### 6-, 12- or 24-fiber jacketed subunits

Quick and easy identification

### Flame-retardant jacket

Rugged and durable



## Standards

### Approvals and Listings

National Electrical Code® (NEC®) OFCP, CSA FT-6, ICEA S-83-596

### Flame Resistance

UL-1666 (for riser and general building applications)



# MIC<sup>®</sup> Unitized Tight-Buffered, Interlocking Armored Cable, Plenum

96 F, 50 µm multimode (OM3)

CORNING

## Specifications

### General Specifications

Environment	Indoor
Application	General Purpose Horizontal, Vertical Riser, Plenum
Cable Type	Tight-Buffered
Product Type	Interlocking armor
Flame Rating	Plenum (OFCP)
Fiber Category	50 µm MM (OM3)

### Temperature Range

Storage	-40 °C to 70 °C (-40 °F to 158 °F)
Installation	0 °C to 60 °C (32 °F to 140 °F)
Operation	0 °C to 70 °C (32 °F to 158 °F)

### Cable Design

Central Element	Jacketed GRP
Fiber Count	96
Number of Active Tubes	4
Subunit Color	Aqua
Number of Fibers per Subunit	24
Subunit Diameter	6.80 mm (0.27 in)
Tight buffer color subunit	Blue, Orange, Green
Tensile Strength Elements and/or Armoring - Layer 1	Dielectric strength members
Tight-Buffer Color Subunit, Layer 1	Brown, Slate, White, Red, Black, Yellow, Violet, Rose, Aqua
Tight Buffer Color Subunit, Layer 2	Blue, Orange, Green, Brown, Slate, White, Red, Black, Yellow, Violet, Rose, Aqua
Number of Ripcords	10
Outer Jacket Material	Flame-retardant
Outer Jacket Color	Aqua

### Mechanical Characteristics Cable

Max. Tensile Strength, Short-Term	660 N (150 lbf)
Max. Tensile Strength, Long-Term	200 N (45 lbf)
Nominal Inner Cable Diameter	22.2 mm (.87 in)
Nominal Outer Diameter	26.2 mm (1.03 in)

# MIC<sup>®</sup> Unitized Tight-Buffered, Interlocking Armored Cable, Plenum

96 F, 50 µm multimode (OM3)

CORNING

## Mechanical Characteristics Cable

Weight	515.3 kg/km (346.27 lb/1000 ft)
Min. Bend Radius Installation	393 mm (15.47 in)
Min. Bend Radius Operation	262 mm (10.31 in)

## Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

## Fiber Specifications

### Optical Characteristics (cabled)

Fiber Core Diameter	50 µm
Fiber Category	OM3
Fiber Code	T
Performance Option Code	80
Wavelengths	850 nm / 1300 nm
Maximum Attenuation	2.8 dB/km / 1.0 dB/km
Serial 1 Gigabit Ethernet	1000 m / 600 m
Serial 10 Gigabit Ethernet	300 m / -
Min. Overfilled Launch (OFL) Bandwidth	1500 MHz*km / 500 MHz*km
Minimum Effective Modal Bandwidth (EMB)	2000 MHz*km / -

## Ordering Information

Part Number	096T88-T3180-A3
Product Description	MIC <sup>®</sup> Unitized Tight-Buffered, Interlocking Armored Cable, Plenum, 96 F, 50 µm multimode (OM3)
EAN Code	4056418172200



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • [www.corning.com/opcomm](http://www.corning.com/opcomm)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/trademarks](http://www.corning.com/opcomm/trademarks). All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2016 Corning Optical Communications. All rights reserved.

CORNING