


MIC[®] 250 Interlocking Armored Distribution Cable, Plenum

144 F, Single-mode (OS2)

CORNING

Corning MIC[®] 250 cables utilize 250 µm color-coded optical fibers surrounded by dielectric strength members with a flexible, flame-retardant outer jacket. These cables are ideal for creating multifiber preconnectorized assemblies as the 12-fiber groupings enable efficient compatibility with multifiber connectors. The flexible, flame-retardant jacket and non-preferential bend axis allow easy installation in space-constrained areas. The core is protected by a flexible, spirally-wrapped, aluminum interlocking armor that offers easy, one-step installation.

This cable is available in 12 different jacket colors – blue, orange, green, brown, slate, white, red, black, yellow, violet, rose and aqua. The colored jacket allows for easy visual identification of the cables. The standard jacket color will be determined by the dominant fiber type in the cable and will use the standard part numbers shown here. Contact Customer Care at 1-800-743-2675 to order other color options.



Part Number: 144ED8-T1301-A3

Features and Benefits

Color-coded fibers

Quick and easy identification

12-fiber groupings

Compatibility with multifiber connectors

Standards

Listings


National Electrical Code[®]
(NEC[®]) OFCP, FT-6, ICEA
S-83-596

Design and Test Criteria

CSA FT-6

Flame Resistance

NFPA 262 (for plenum, riser and general building applications)



Cross Section of Part Number: 144ED8-T1301-A3

Specifications

General Specifications	
Environment	Indoor
Application	General Purpose Horizontal, Vertical Riser, Plenum
Cable Type	Loose Tube
Product Type	Distribution

MIC[®] 250 Interlocking Armored Distribution Cable, Plenum

144 F, Single-mode (OS2)

CORNING

General Specifications

Flame Rating	Plenum (OFNP)
Fiber Category	Single-mode (OS2)

Temperature Range

Storage	-40 °C to 70 °C (-40 °F to 158 °F)
Installation	0 °C to 60 °C (32 °F to 140 °F)
Operation	0 °C to 70 °C (32 °F to 158 °F)

Cable Design

Fiber Count	144
Fibers per Subunit	12
Fiber Coloring	Blue, Orange, Green, Brown, Slate, White, Red, Black, Yellow, Violet, Rose, Aqua
Tensile Strength Elements and/or Armoring - Layer 1	Dielectric strength members
Subunit Jacket Material	Flame-retardant
Subunit Color	Yellow
Number of Subunits Layer 1	3
Number of Subunits Layer 2	9
Number of Ripcords	1
Outer Jacket Material	Flame-retardant
Outer Jacket Color	Yellow

Mechanical Characteristics Cable

Weight	403.22 kg/km (270.95 lb/1000 ft)
Nominal Outer Diameter	23.7 mm (0.93 in)
Max. Tensile Strength, Short-Term	660 N (150 lbf)
Max. Tensile Strength, Long-Term	200 N (45 lbf)
Min. Bend Radius Installation	355.5 mm (14.0 in)
Min. Bend Radius Operation	237 mm (9.3 in)

Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

MIC[®] 250 Interlocking Armored Distribution Cable, Plenum

144 F, Single-mode (OS2)



Fiber Specifications

Optical Characteristics (cabled)	
Fiber Name	Single-mode (OS2)
Fiber Category	G.652.D
Fiber Code	E
Performance Option Code	01
Wavelengths	1310 nm / 1383 nm / 1550 nm
Maximum Attenuation	0.4 dB/km / 0.4 dB/km / 0.3 dB/km

Ordering Information

Part Number	144ED8-T1301-A3
Product Description	MIC [®] 250 Distribution Cable, Plenum, Interlocking Armor, 144 F, Single-mode (OS2)
EAN Code	4056418169163



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2016 Corning Optical Communications. All rights reserved.

