

FC to FC Patch cord, 2 fibres, Zipcord Tight-Buffered Cable, LSZH, 2.8 mm legs

62.5 µm multimode (OM1), 9 m

CORNING

Patch cables are used for non-permanent connections between patch panels, transmission equipment, etc. Pre-assembled cables allow for the implementation of complete Plug & Play solutions. When such a solution is adopted with accurate dimensioning and appropriate cable routing, it is possible to install even large cabling systems rapidly.

Features and Benefits

Connectors

- FC connector according to TIA/EIA-604 -4
- All connectors are tested to FOTP -21.
- Connectors are pre-radius polished to provide the optimal end-face geometry for long-term performance.

Cable

- Low smoke (IEC 61034) and zero-halogen (LSZH), flame retardant to IEC 60332-3-24 (C) and noncorrosive to IEC 60754-2 (FRNC)
- Cables are metal free; hence, there are no ground-loop or potential-equalization problems. Completely dry design (without gel)
- Colour of outer sheath: OM1, OM2 – orange; OM3, OM4 – turquoise; OS2 – yellow

Standards

Intermateability TIA/EIA-604-4 / TIA/EIA-604-4

Specifications

| General Specifications | |
|------------------------|------------------|
| Flame rating | LSZH™/FRNC |
| Cable assembly type | Two Fibre |
| Fibre Category | 62.5 µm MM (OM1) |

| Temperature Range | |
|---------------------------|-----------------|
| Operation | -10 °C to 60 °C |
| Installation and assembly | -5 °C to 50 °C |
| Storage | -10 °C to 60 °C |

FC to FC Patch cord, 2 fibres, Zipcord Tight-Buffered Cable, LSZH, 2.8 mm legs

62.5 µm multimode (OM1), 9 m

CORNING

Design - Connector A

| | |
|------------------|------------|
| Connector type | FC |
| Ferrule Material | Ceramic |
| Polish | PC |
| Housing material | Metal |
| Housing Colour | Nickel |
| Boot type | Individual |
| Boot colour | Black |
| Keyed (security) | No |

Mechanical Specifications - Connector A

| | |
|---------------------------------|----------------------------------|
| Durability | ≤ 0.2 dB 1000 rematings, FOTP-21 |
| Tensile strength jacketed cable | 44 N |

Optical Specifications - Connector A

| | |
|-------------------------|---------|
| Insertion loss, typical | 0.35 dB |
| Insertion loss, max. | 0.5 dB |

Design - Connector B

| | |
|------------------|------------|
| Boot colour | Black |
| Connector type | FC |
| Ferrule Material | Ceramic |
| Polish | PC |
| Housing material | Metal |
| Housing Colour | Nickel |
| Boot type | Individual |
| Keyed (security) | No |

Mechanical Specifications - Connector B

| | |
|---------------------------------|----------------------------------|
| Durability | ≤ 0.2 dB 1000 rematings, FOTP-21 |
| Tensile strength jacketed cable | 44 N |

FC to FC Patch cord, 2 fibres, Zipcord Tight-Buffered Cable, LSZH, 2.8 mm legs

62.5 µm multimode (OM1), 9 m

CORNING

Optical Specifications - Connector B

| | |
|-------------------------|---------|
| Insertion loss, typical | 0.35 dB |
| Insertion loss, max. | 0.5 dB |

Cable Design

| | |
|-------------------------------|-----------------|
| Fibre count | 2 |
| Outer diameter | 2.8 mm x 5.7 mm |
| Outer jacket colour | Orange |
| Outer jacket material | LSZH™/FRNC |
| Minimum Bend Radius | 30 mm |
| Crush resistance (reversible) | 1000 N/10 cm |
| Tensile strength | 400 N |

Chemical Characteristics

| | |
|------|---|
| RoHS | Free of hazardous substances according to RoHS 2011/65/EU |
|------|---|

Fibre Specifications

Optical Characteristics (cabled)

| | |
|---|---------------------------|
| Fibre name | G62.5L/125 InfiniCor® 300 |
| Fibre code | K |
| Fibre core diameter | 62.5 µm |
| Fibre Category | OM1 |
| Wavelengths | 850 nm / 1300 nm |
| Maximum attenuation | 3.1 dB/km / 0.8 dB/km |
| Typical attenuation | 2.9 dB/km / 0.7 dB/km |
| Serial 1 gigabit ethernet | 300 m / 550 m |
| Serial 10 gigabit ethernet | 33 m / - |
| Min. overfilled launch (OFL) bandwidth | 200 MHz*km / 600 MHz*km |
| Minimum effective modal bandwidth (EMB) | 220 MHz*km / - |

- Notes:
- 1) Improved attenuation and bandwidth options available
 - 2) Bend-insensitive single-mode fibres available on request.
 - 3) Contact a Corning Customer Care Representative for additional information

FC to FC Patch cord, 2 fibres, Zipcord Tight-Buffered Cable, LSZH, 2.8 mm legs

62.5 µm multimode (OM1), 9 m



Ordering Information

| | |
|---------------------|--|
| Part Number | 171702K5Z41009M |
| Product Description | FC to FC patch cord on 2-fibres Zipcord cable, with 2.8 mm legs, and a low-smoke, zero-halogen sheath. Length is variable. |
| EAN Code | 4056418606422 |
| Length | 9 m |
| Weight | 0.154 kg |

Shipping Information

| | |
|--------------------------------|--------------------------|
| Packing type | Cardboard box |
| Packing dimensions (L x W x H) | 380 mm x 250 mm x 180 mm |
| Units Per Delivery | 1/1 |



Corning Optical Communications GmbH & Co. KG · Leipziger Strasse 121 · 10117 Berlin, GERMANY
00 800 2676 4641 · FAX: +49 30 5303 2335 · www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified.
© 2018 Corning Optical Communications. All rights reserved.