

FC to FC Patch cord, 2 fibres, Zipcord Tight-Buffered Cable, LSZH, 2.8 mm legs

62.5 µm multimode (OM1), 10 m

CORNING

Patch cables are used for non-permanent connections between patch panels, transmission equipment, etc. Pre-assembled cables allow for the implementation of complete Plug & Play solutions. When such a solution is adopted with accurate dimensioning and appropriate cable routing, it is possible to install even large cabling systems rapidly.

Features and Benefits

Connectors

- FC connector according to TIA/EIA-604 -4
- All connectors are tested to FOTP -21.
- Connectors are pre-radius polished to provide the optimal end-face geometry for long-term performance.

Cable

- Low smoke (IEC 61034) and zero-halogen (LSZH), flame retardant to IEC 60332-3-24 (C) and noncorrosive to IEC 60754-2 (FRNC)
- Cables are metal free; hence, there are no ground-loop or potential-equalization problems. Completely dry design (without gel)
- Colour of outer sheath: OM1, OM2 – orange; OM3, OM4 – turquoise; OS2 – yellow

Standards

Intermateability TIA/EIA-604-4 / TIA/EIA-604-4

Specifications

General Specifications	
Flame rating	LSZH™/FRNC
Cable assembly type	Two Fibre
Fibre Category	62.5 µm MM (OM1)

Temperature Range	
Operation	-10 °C to 60 °C
Installation and assembly	-5 °C to 50 °C
Storage	-10 °C to 60 °C

FC to FC Patch cord, 2 fibres, Zipcord Tight-Buffered Cable, LSZH, 2.8 mm legs

62.5 µm multimode (OM1), 10 m

CORNING

Design - Connector A

Connector type	FC
Ferrule Material	Ceramic
Polish	PC
Housing material	Metal
Housing Colour	Nickel
Boot type	Individual
Boot colour	Black
Keyed (security)	No

Mechanical Specifications - Connector A

Durability	≤ 0.2 dB 1000 rematings, FOTP-21
Tensile strength jacketed cable	44 N

Optical Specifications - Connector A

Insertion loss, typical	0.35 dB
Insertion loss, max.	0.5 dB

Design - Connector B

Boot colour	Black
Connector type	FC
Ferrule Material	Ceramic
Polish	PC
Housing material	Metal
Housing Colour	Nickel
Boot type	Individual
Keyed (security)	No

Mechanical Specifications - Connector B

Durability	≤ 0.2 dB 1000 rematings, FOTP-21
Tensile strength jacketed cable	44 N

FC to FC Patch cord, 2 fibres, Zipcord Tight-Buffered Cable, LSZH, 2.8 mm legs

62.5 µm multimode (OM1), 10 m

CORNING

Optical Specifications - Connector B

Insertion loss, typical	0.35 dB
Insertion loss, max.	0.5 dB

Cable Design

Fibre count	2
Outer diameter	2.8 mm x 5.7 mm
Outer jacket colour	Orange
Outer jacket material	LSZH™/FRNC
Minimum Bend Radius	30 mm
Crush resistance (reversible)	1000 N/10 cm
Tensile strength	400 N

Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

Fibre Specifications

Optical Characteristics (cabled)

Fibre name	G62.5L/125 InfiniCor® 300
Fibre code	K
Fibre core diameter	62.5 µm
Fibre Category	OM1
Wavelengths	850 nm / 1300 nm
Maximum attenuation	3.1 dB/km / 0.8 dB/km
Typical attenuation	2.9 dB/km / 0.7 dB/km
Serial 1 gigabit ethernet	300 m / 550 m
Serial 10 gigabit ethernet	33 m / -
Min. overfilled launch (OFL) bandwidth	200 MHz*km / 600 MHz*km
Minimum effective modal bandwidth (EMB)	220 MHz*km / -

- Notes:
- 1) Improved attenuation and bandwidth options available
 - 2) Bend-insensitive single-mode fibres available on request.
 - 3) Contact a Corning Customer Care Representative for additional information

FC to FC Patch cord, 2 fibres, Zipcord Tight-Buffered Cable, LSZH, 2.8 mm legs

62.5 µm multimode (OM1), 10 m



Ordering Information

Part Number	171702K5Z41010M
Product Description	FC to FC patch cord on 2-fibres Zipcord cable, with 2.8 mm legs, and a low-smoke, zero-halogen sheath. Length is variable.
EAN Code	4056418606439
Length	10 m
Weight	0.17 kg

Shipping Information

Packing type	Cardboard box
Packing dimensions (L x W x H)	380 mm x 250 mm x 180 mm
Units Per Delivery	1/1



Corning Optical Communications GmbH & Co. KG · Leipziger Strasse 121 · 10117 Berlin, GERMANY
00 800 2676 4641 · FAX: +49 30 5303 2335 · www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified.
© 2018 Corning Optical Communications. All rights reserved.