

# FREEDM® Ribbon, Gel-Filled Cable, Riser

216 F, 62.5 μm multimode (OM1)

CORNING

Corning FREEDM® ribbon riser cables are lightweight cables designed for indoor/outdoor installations such as campus backbones in aerial, duct and riser applications. A UV-resistant, flame-retardant jacket allows added flexibility in placing this cable outdoors, whether it is an aerial, duct or direct-buried application, or indoor general horizontal or riser applications.

The cable consists of a ribbon stack of 12-fiber ribbons within a gel-filled central buffer tube. With easily accessible individual 250 μm colored fibers, the ribbons have readily identifiable ribbon ID numbers and fiber colors. The precise fiber and ribbon geometries result in excellent mass splicing yields. Surrounding the tube are dielectric strength members that provide tensile strength and innovative waterblocking tapes that reduce cable weight and preparation time. This design is also compatible with standard ribbon cable procedures and hardware for easy field installation and reduced labor costs.

*Note: This cable is available in 12 different jacket colors – blue, orange, green, brown, slate, white, red, black, yellow, violet, rose and aqua. The colored jacket allows for easy visual identification of the cables while still providing all of the required environmental protection of an indoor/outdoor cable jacket. Black is the standard jacket color using the part numbers shown here. Contact Customer Care at 1-800-743-2675 to order other color options.*

## Features and Benefits

### Precise fiber and ribbon geometries

Excellent mass splicing yields

### Waterblocked cable

Enables use of cables for outdoor applications

### 12-fiber ribbons with ribbon IDs

Easy identification

### UV-resistant, flame-retardant jacket



Rugged, durable and easy to strip

### Available in preconnectorized assemblies

Easy field installation and reduced labor costs

### Common installations

Outdoor aerial and duct; indoor vertical riser and general purpose horizontal according to NEC Article 770



# FREEDM<sup>®</sup> Ribbon, Gel-Filled Cable, Riser

216 F, 62.5  $\mu$ m multimode (OM1)

CORNING

## Standards

<b>Listings</b>	National Electrical Code <sup>®</sup> (NEC <sup>®</sup> ) OFNR, FT-4
<b>Design and Test Criteria</b>	ANSI/ICEA S-104-696, CSA OFN FT-4

## Specifications

General Specifications	
Environment	Indoor/Outdoor Cables
Application	Aerial, Direct Buried, Duct, General Purpose Horizontal, (Vertical Riser)
Cable Type	Ribbon
Product Type	Dielectric
Flame Rating	Riser (OFNR)
Fiber Category	62.5 $\mu$ m MM (OM1)

Temperature Range	
Storage	-40 °C to 70 °C (-40 °F to 158 °F)
Installation	-10 °C to 60 °C (14 °F to 140 °F)
Operation	-40 °C to 70 °C (-40 °F to 158 °F)

Cable Design	
Fiber Count	216
Ribbons per Tube	18
Fibers per Ribbon	12
Fiber Coloring	Blue, Orange, Green, Brown, Slate, White, Red, Black, Yellow, Violet, Rose, Aqua
Buffer Tube Color	Natural
Buffer Tube Diameter	10.5 mm (0.41 in)
Tensile Strength Elements and/or Armoring - Layer 1	Dielectric strength members
Tape	Water-swellable
Tape, Layer 2	Flame-retardant tape
Tape, Layer 3	Water-swellable
Tensile Strength Elements and/or Armoring - Layer 2	Dielectric strength members
Number of Ripcords	2

# FREEDM<sup>®</sup> Ribbon, Gel-Filled Cable, Riser

216 F, 62.5  $\mu$ m multimode (OM1)

CORNING

## Cable Design

Outer Jacket Material	Flame-Retardant, UV-Resistant
Outer Jacket Color	Black

## Mechanical Characteristics Cable

Max. Tensile Strength, Short-Term	2700 N (600 lbf)
Max. Tensile Strength, Long-Term	600 N (135 lbf)
Weight	286 kg/km (192 lb/1000 ft)
Nominal Outer Diameter	17.6 mm (0.69 in)
Min. Bend Radius Installation	264 mm (10.4 in)
Min. Bend Radius Operation	176 mm (6.9 in)

## Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

## Fiber Specifications

### Optical Characteristics (cabled)

Fiber Core Diameter	62.5 $\mu$ m
Fiber Category	OM1
Fiber Code	K
Performance Option Code	30
Wavelengths	850 nm / 1300 nm
Maximum Attenuation	3.4 dB/km / 1.0 dB/km
Serial 1 Gigabit Ethernet	300 m / 550 m
Serial 10 Gigabit Ethernet	33 m / -
Min. Overfilled Launch (OFL) Bandwidth	200 MHz*km / 500 MHz*km
Minimum Effective Modal Bandwidth (EMB)	220 MHz*km / -

Notes: 1) Improved attenuation and bandwidth options available.  
2) Bend-insensitive single-mode fibers available on request.  
3) Contact a Corning Customer Care Representative for additional information.

CORNING

# FREEDM® Ribbon, Gel-Filled Cable, Riser

216 F, 62.5 µm multimode (OM1)



## Ordering Information

Part Number	216KCF-14130-20
Product Description	FREEDM® Ribbon, Gel-Filled Cable, Riser, 216 F, 62.5 µm multimode (OM1)
EAN Code	4056418162911



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • [www.corning.com/opcomm](http://www.corning.com/opcomm)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/trademarks](http://www.corning.com/opcomm/trademarks).

All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2016 Corning Optical Communications. All rights reserved.

