


Corning SOLO® ADSS optical cables are all-dielectric, self-supporting (ADSS) cables designed for easy and economical one-step installation in campus backbones with self-supporting installations where metallic messengers cannot be used. The loose tube design provides stable performance over a wide temperature range and is compatible with any telecommunications-grade optical fiber. The cable design can span distances in excess of 500 m (1650 ft) in NESC heavy conditions.

This cable incorporates innovative waterblocking materials, eliminating the need for traditional flooding compound and providing efficient and craft-friendly cable preparation. While the concentric, self-supporting cable design allows easy, one-step installation using standard hardware and installation methods, the SZ-stranded, loose tube design isolates optical fibers from installation and environmental rigors and facilitates mid-span access. The ADSS optical cables are also available with a proprietary track-resistant polyethylene (TRPE) jacket suitable for installation in electric field potentials up to 25 kV.



Part Number: 288EAE-T4A01A20

Features and Benefits

Stable performance and compatibility with all common fiber types

Easy, one-step installation

Suitable for installations up to 25 kV electric field potential


Provides efficient and craft-friendly cable preparation

Standards

USDA Rural Development Programs

Outdoor self-supporting aerial

ANSI/ICEA S-87-640



Cross Section of Part Number: 288EAE-T4A01A20

Specifications

Environment	Outdoor
Application	Self-Supporting
Cable Type	Loose Tube
Product Type	Self-Supporting
Fiber Category	Single-mode (OS2)

Storage	-40 °C to 75 °C (-40 °F to 167 °F)
Installation	-30 °C to 70 °C (-22 °F to 158 °F)
Operation	-40 °C to 70 °C (-40 °F to 158 °F)

Central Element	Dielectric
Fiber Count	288
Fiber Coloring	Blue, Orange, Green, Brown, Slate, White, Red, Black, Yellow, Violet, Rose, Aqua
Fibers per Tube	12
Number of Tube Positions	24
Number of Active Tubes	24
Buffer Tube Color Coding, Layer 1	Blue, Orange, Green, Brown, Slate, White, Red, Black, Yellow
Buffer Tube Diameter	2.85 mm (0.11 in)
Tape	Water-swellaable
Buffer Tube Color Coding, Layer 2	Violet, Rose, Aqua, Blue*, Orange*, Green*, Brown*, Slate*, White*, Red*, Black*, Yellow*, Violet*, Rose*, Aqua*
Tape, Layer 2	Water-swellaable
Inner Jacket Material	Polyethylene (PE)
Tensile Strength Elements and/or Armoring - Layer 1	Dielectric strength members
Number of Ripcords	3
Outer Jacket Material	Polyethylene (PE)
Outer Jacket Color	Black

Weight	449 kg/km (302 lb/1000 ft)
Nominal Outer Diameter	24.8 mm (0.98 in)
Min. Bend Radius Installation	372 mm (14.7 in)
Min. Bend Radius Operation	248 mm (9.8 in)
Span Code	A

Span m (ft)	Initial Installation		NESC Light		NESC Medium		NESC Heavy	
	SAG %	Tension N (lbf)	SAG %	Tension N (lbf)	SAG %	Tension N (lbf)	SAG %	Tension N (lbf)
305 (1000)	1	16596 (3734)	1.2	18729 (4214)	2.4	20169 (4538)	3.4	25702 (5783)
335 (1100)	1	18258 (4108)	1.2	20471 (4606)	2.5	21982 (4946)	3.4	27827 (6261)
366 (1200)	1	19916 (4481)	1.2	22209 (4997)	2.5	23782 (5351)	3.5	29920 (6732)
396 (1300)	1	21578 (4855)	1.2	23942 (5387)	2.5	25573 (5754)	3.5	31987 (7197)
427 (1400)	1	23236 (5228)	1.2	25667 (5775)	2.5	27356 (6155)	-	
457 (1500)	1	24898 (5602)	1.3	27387 (6162)	2.5	29129 (6554)	-	
488 (1600)	1	26556 (5975)	1.3	29102 (6548)	2.5	30893 (6951)	-	
518 (1700)	1	28213 (6348)	1.3	30818 (6934)	-		-	
549 (1800)	1	29876 (6722)	1.3	32524 (7318)	-		-	

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

Fiber Specifications

Fiber Name	Single-mode (OS2)
Fiber Category	G.652.D
Fiber Code	E
Performance Option Code	01
Wavelengths	1310 nm / 1383 nm / 1550 nm
Maximum Attenuation	0.4 dB/km / 0.4 dB/km / 0.3 dB/km

Ordering Information

Part Number	288EAE-T4A01A20
Product Description	SOLO® ADSS Loose Tube, Gel-Filled, Dual-Jacket Cable, Span Code A, 288 F, Single-mode (OS2)



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2016 Corning Optical Communications. All rights reserved.