

# UltraRibbon™ Riser Gel-Free Cable

432 F, 50 μm multimode (OM4)

CORNING

Corning UltraRibbon™ Riser Gel-Free Cables continue the innovative breakthrough in indoor cable technology with a new generation of high-fiber-count single tube cables. Providing up to 432 fibers in a rugged, compact design, the cable maximizes the use of critical duct space and can easily fit in 1.25-in inner duct. A specially formulated flame-retardant jacket allows this cable to be used in indoor general purpose horizontal and riser applications.

The cable consists of a single buffer tube containing a stack of up to eighteen 24-fiber ribbons. The 24-fiber ribbons can be easily separated by hand into two 12-fiber ribbons. The 12-fiber ribbons have readily identifiable ribbon IDs, fiber colors, and precise geometries that result in excellent mass-splicing yields.

## Features and Benefits

### Each 12-fiber ribbon individually numbered

Easy identification

### Precise fiber and ribbon geometries in a gel-free design

Excellent mass splicing yields

### Flame-retardant jacket

Rugged and durable

### Up to 432 fibers in a compact design



Easily fits in 1.25-in diameter inner duct

### Common installations

Indoor vertical riser and general purpose horizontal according to National Electrical Code® (NEC®) Article 770

## Standards

<b>Listings</b>	National Electrical Code® (NEC®) OFNR
<b>Design Criteria</b>	CSA FT-4
<b>Test Criteria</b>	ANSI/ICEA S-83-596



# UltraRibbon™ Riser Gel-Free Cable

432 F, 50 µm multimode (OM4)

CORNING

## Specifications

General Specifications	
Environment	Indoor
Application	General Purpose Horizontal, Vertical Riser
Cable Type	Ribbon
Product Type	Distribution
Flame Rating	Riser (OFNR)
Fiber Category	50 µm MM (OM4)

Temperature Range	
Storage	-40 °C to 70 °C (-40 °F to 158 °F)
Installation	-10 °C to 60 °C (14 °F to 140 °F)
Operation	-20 °C to 70 °C (-4 °F to 158 °F)

Cable Design	
Fiber Count	432
Ribbons per Tube	18
Fibers per Ribbon	24
Fiber Coloring	Blue, Orange, Green, Brown, Slate, White, Red, Black, Yellow, Violet, Rose, Aqua
Buffer Tube Color	Natural
Buffer Tube Diameter	15.4 mm (0.60 in)
Tape	Waterblocking foam tape
Tensile Strength Elements and/or Armoring - Layer 1	Dielectric strength members
Number of Ripcords	2
Outer Jacket Material	Flame-retardant
Outer Jacket Color	Aqua

Mechanical Characteristics Cable	
Max. Tensile Strength, Short-Term	1320 N (300 lbf)
Max. Tensile Strength, Long-Term	400 N (90 lbf)
Weight	351 kg/km (235 lb/1000 ft)
Nominal Outer Diameter	21.5 mm (0.85 in)
Min. Bend Radius Installation	323 mm (12.7 in)
Min. Bend Radius Operation	215 mm (8.5 in)

CORNING

# UltraRibbon™ Riser Gel-Free Cable

432 F, 50 µm multimode (OM4)

CORNING

## Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2002/95/EG
------	---

## Fiber Specifications

### Optical Characteristics (cabled)

Fiber Core Diameter	50 µm
Fiber Category	OM4
Fiber Code	T
Performance Option Code	90
Wavelengths	850 nm / 1300 nm
Maximum Attenuation	3.0 dB/km / 1.0 dB/km
Serial 1 Gigabit Ethernet	1100 m / 600 m
Serial 10 Gigabit Ethernet	550 m / -
Min. Overfilled Launch (OFL) Bandwidth	3500 MHz*km / 500 MHz*km
Minimum Effective Modal Bandwidth (EMB)	4700 MHz*km / -

\* Assumes 1.0 dB maximum total connector/splice loss.

\* Meets 0.75 ns optical skew when used in all Corning Plug and Play™/EDGE™ systems solutions.

- Notes:
- 1) 50 µm multimode fiber macrobend loss  $\leq 0.2$  dB at 850 nm for two turns around 7.5 mm radius mandrel.
  - 2) Improved attenuation and bandwidth options available.
  - 3) Bend-insensitive single-mode fibers available on request.
  - 4) Contact a Corning Customer Care Representative for additional information.

## Ordering Information

Part Number	432TV7-14190D20
Product Description	UltraRibbon™ Riser Gel-Free Cable, 432 F, 50 µm multimode (OM4)
EAN Code	4056418145631



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • [www.corning.com/opcomm](http://www.corning.com/opcomm)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/trademarks](http://www.corning.com/opcomm/trademarks). All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2016 Corning Optical Communications. All rights reserved.

CORNING