


LSZH™ UltraRibbon™ Indoor Gel-Filled Cables

504 F, Single-mode (OS2)

CORNING

Corning LSZH™ UltraRibbon™ cables are designed for horizontal intrabuilding backbones where limited-smoke and zero-halogen requirements exist. These cables are organized with 12-fiber ribbons inside a central tube that are surrounded by dielectric strength members and a specially formulated flame-retardant outer jacket. The 12-fiber ribbons have readily identifiable ribbon ID numbers and fiber colors that allow for easy access to individual fibers. The precise fiber and ribbon geometries result in excellent mass splicing yields. The ribbon riser cables are compatible with standard ribbon cable procedures and hardware.

This cable is available in 12 different jacket colors – blue, orange, green, brown, slate, white, red, black, yellow, violet, rose and aqua. The colored jacket allows for easy visual identification of the cables. The standard jacket color will be determined by the dominant fiber type in the cable and will use the standard part numbers shown here. Contact Customer Care at 1-800-743-2675 to order other color options.



Features and Benefits

288 up to 864 fibers in a compact design gel-filled design

Maximizes use of critical duct space

Hand-splittable ribbon


Facilitates mass-fusion splicing with 12-fiber units and no stray fibers

12-fiber ribbons individually numbered

Easy identification

Fiber and ribbon geometries

Provide excellent mass fusion splicing results



Standards

Approvals and Listings

National Electrical Code®
(NEC®) OFN-LS, CSA OFN
FT-4

Design and Test Criteria

ANSI/ICEA S-104-696,
Telcordia GR-409 and GR-
20

LSZH™ UltraRibbon™ Indoor Gel-Filled Cables

504 F, Single-mode (OS2)

CORNING

Specifications

General Specifications	
Environment	Indoor
Application	Aerial, Direct Buried, Duct, General Purpose Horizontal
Cable Type	Ribbon
Flame Rating	LSZH™ (OFN-LS)
Fiber Category	Single-mode (OS2)

Temperature Range	
Storage	-40 °C to 70 °C (-40 °F to 158 °F)
Installation	-10 °C to 60 °C (14 °F to 140 °F)
Operation	-40 °C to 70 °C (-40 °F to 158 °F)

Cable Design	
Fiber Count	504
Ribbons per Tube	14
Fibers per Ribbon	36
Fiber Coloring	Blue, Orange, Green, Brown, Slate, White, Red, Black, Yellow, Violet, Rose, Aqua
Buffer Tube Color	Natural
Buffer Tube Diameter	17.9 mm (0.7 in)
Tensile Strength Elements and/or Armoring - Layer 1	Dielectric strength members
Tape	Water-swellable
Tape, Layer 2	Flame-retardant tape
Tape, Layer 3	Water-swellable
Number of Ripcords	2
Outer Jacket Material	Flame-Retardant, UV-Resistant
Outer Jacket Color	Yellow

Mechanical Characteristics Cable	
Max. Tensile Strength, Short-Term	2700 N (600 lbf)
Max. Tensile Strength, Long-Term	890 N (200 lbf)
Weight	570 kg/km (383 lb/1000 ft)

LSZH™ UltraRibbon™ Indoor Gel-Filled Cables

504 F, Single-mode (OS2)



Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2002/95/EG
------	---

Fiber Specifications

Optical Characteristics (cabled)

Fiber Name	Single-mode (OS2)
Fiber Category	G.652.D
Fiber Code	E
Performance Option Code	01
Wavelengths	1310 nm / 1383 nm / 1550 nm
Maximum Attenuation	0.4 dB/km / 0.4 dB/km / 0.3 dB/km

Ordering Information

Part Number	504EVJ-14101-20
Product Description	LSZH™ UltraRibbon™ Gel-Filled Indoor Cable, 504 F, Single-mode (OS2)



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2015 Corning Optical Communications. All rights reserved.

Corning Optical Communications RF LLC (Corning Gilbert) • 5310 W. Camelback Rd. • Glendale, AZ 85301 USA

800-528-5567 • FAX: 602-844-6358 • International: +1-623-245-1050 • www.corning.com/gilbert

Page 3 | Revision date 2015-11-08

A complete listing of the trademarks of Corning Optical Communications RF is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications RF is ISO 9001

