

FutureCom™ EA Patch Cord, FRNC, RJ45 - RJ45 connector Blue, RJ45-RJ45 connector, 1 m



Part Number:
CCAAGB-G2002-A010-C0

The application-neutral FutureCom™ category 6A patch cords have four individual foil-shielded pairs (PiMF) and an additional braid shield (S/FTP). They are assembled with a shielded RJ45 connectors on each end. The zero halogen patch cords (LSZH) are non-corrosive according to IEC 60754-2 (FRNC) and EN 50267, low smoke according to IEC 61034 and EN 50268 and flame retardant according to IEC 60332-1, Category B and EN 50266-2-1. FutureCom™ S500 patch cords provide additional latch protection.

They are available in various lengths and colors.

Features and Benefits

S/FTP flex cable, Category 7

Application-neutral due to using all four pairs of RJ45 connectors

Minimum surface transfer impedance of cable (<10 mΩ/m at 10 MHz)

Outstanding transmission characteristics according to 10GBase-T

Additional latch protection

Category 6A

PVP Certificate

Tested and approved for use according to IEEE802.3.bt



FutureCom™ EA Patch Cord, FRNC, RJ45 - RJ45 connector Blue, RJ45-RJ45 connector, 1 m



Specifications

General Specifications	
Product category	Core product / Fastship
Cable assembly type	Patch cords
Environment	Indoor
Category	6A
Cable type	S/FTP
Halogen-free	Yes

Electrical Specifications	
Max. loop resistance	43 Ω/km
Delay skew	290 ns/100 m
Earth coupling at 0.001 MHz	20 pF/km
Propagation delay	≥10 MHz 1600 ns/m
DC resistance unbalance	4.3 %
Impedance Z0 at 101-250 MHz	100 Ω ± 18%
Impedance Z0 at 251-600 MHz	100 Ω ± 25%
Mutual capacity	43 pF/m
Insulation resistance	5000 MΩ*km

Specifications - Connector A	
Connector type	RJ45 - 8/8
Durability Cycles	750 N/A

Cable Design	
Conductor insulation	Halogen-free foam-skin material
Conductor	Copper Wire, AWG 26

FutureCom™ EA Patch Cord, FRNC, RJ45 - RJ45 connector Blue, RJ45-RJ45 connector, 1 m



Cable Design	
Twisting	2 cores to a pair
Pair screen	Al-laminated foil around each pair
Overall screen	Copper braid, tinned
Outer jacket material	LSZH™/FRNC
Outer jacket colour	Blue

Specifications - Connector B	
Connector type	RJ45 - 8/8
Durability Cycles	750 N/A

Standards	
RoHS	Free of hazardous substances according to RoHS 2011/65/EU

Environmental Conditions	
Temperature range, operation	-20 °C to 60 °C

Mechanical Specifications	
Min. bend radius installation	47 mm



Corning Optical Communications GmbH & Co. KG • Leipzig Strasse 121 • 10117 Berlin, Germany
+00 800 2675 4641 • FAX: +49 30 5303 2335 • www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2021 Corning Optical Communications. All rights reserved.