

# EDGE™ Housing

1 rack unit, holds up to 8 EDGE modules or panels

CORNING

EDGE™ HD solutions are high-density preterminated optical cabling solutions offering industry-leading connector density. With unprecedented finger access, there is no need for additional tools enabling faster moves, adds and changes (MACs).

## Features and Benefits

### Universal wired components

Enable moves, adds and changes without polarity concerns; provide a simple migration path between 2-fibre and parallel optic applications

### Sliding drawers

Allow unprecedented finger access, easier jumper/harness routing and port identification

### Integrated strain-relief plate can rotate 90°

Allows for rear cable entry direction, as well as the traditional side cable entry

### Removable top covers on the 1 U and 2 U housings

Provide easier access to modules and panels



## Specifications

General Specifications	
Application	Data Centre, Data Centre LAN/SAN, Enterprise Networks
Product type	Fibre Optic Hardware
Mounting type	Rack Mount, Cabinet-mount
Mounting Technology	Adjustable depth settings
Access type	Front and rear access slidable
Lockable	Yes, rear side

Design - Hardware	
Housing type	EDGE™ HD
Height Unit	1U
Number of Panels per Housing	8
Housing Colour	Silver
Fibre Capacity	96
Cable Entry Direction	Rear
Cable entry type	Side brush entry

# EDGE™ Housing

1 rack unit, holds up to 8 EDGE modules or panels

CORNING

## Design - Hardware

Colour	Silver
Number of modules	8

## Mechanical Characteristics

Dimensions (W x D x H)	432 mm x 561 mm x 44 mm (17 in x 22.1 in x 1.75 in)
Weight	5.4 kg (12 lb)
Minimum Cabinet Size	600 mm

## Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2002/95/EG
------	---

## Ordering Information

Part Number	EDGE-01U
Product Description	EDGE™ Housing, 1 rack unit, holds up to 8 EDGE modules or panels
EAN Code	4056418143071
Module Capacity	8
Trunk Capacity	12 (size 1 or 2)

## Shipping Information

Units Per Delivery	1/1
Packaging Dimensions (W x D x H)	565 mm x 657 mm x 171 mm (20.3 in x 27 in x 7.8 in)
Shipping Weight	7.7 kg (17 lb)



Corning Optical Communications GmbH & Co. KG · Leipziger Strasse 121 · 10117 Berlin, GERMANY  
00 800 2676 4641 · FAX: +49 30 5303 2335 · [www.corning.com/opcomm/emea](http://www.corning.com/opcomm/emea)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/emea/trademarks](http://www.corning.com/opcomm/emea/trademarks). Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2016 Corning Optical Communications. All rights reserved.