

# EDGE™ Housing

2 rack unit, holds up to 24 EDGE modules or panels

CORNING

EDGE™ HD solutions are high-density preterminated optical cabling solutions offering industry-leading connector density. With unprecedented finger access, there is no need for additional tools enabling faster moves, adds and changes (MACs).

## Features and Benefits

### Universal wired components

Enable moves, adds and changes without polarity concerns; provide a simple migration path between 2-fiber and parallel optic applications

---

### Revolutionary drawer-style hardware

Offers unprecedented finger access while achieving the highest port density in the market

---

### Rotatable trunk strain relief parking plates

Allows for rear cable entry direction, as well as the traditional side cable entry

---

### Padlockable hasp on rear cover

Allows for customer provided padlock and enhanced security



# EDGE™ Housing

2 rack unit, holds up to 24 EDGE modules or panels

CORNING

## Specifications

General Specifications	
Application	Data Center, Data Center LAN/SAN, Enterprise Networks
Product Type	Fiber Optic Hardware
Mounting Type	Rack Mount, Cabinet-mount
Mounting Technology	Adjustable depth settings
Access Type	Front and rear access slidable
Lockable	Yes, rear side

Design - Hardware	
Housing Type	EDGE™ HD
Height Unit	2U
Number of Panels per Housing	24
Housing Color	Silver
Fiber Capacity	288
Cable Entry Direction	Rear
Cable entry type	Side brush entry
Color	Silver
Number of Modules	24

Mechanical Characteristics	
Dimensions (W x D x H)	432 mm x 561 mm x 88 mm (17 in x 22.1 in x 3.5 in)
Weight	8.6 kg (19 lb)
Minimum Cabinet Size	800 mm

Chemical Characteristics	
RoHS	Free of hazardous substances according to RoHS 2002/95/EG

# EDGE™ Housing

2 rack unit, holds up to 24 EDGE modules or panels



## Ordering Information

Part Number	EDGE-02U
Product Description	EDGE™ Housing, 2 rack unit, holds up to 24 EDGE modules or panels
EAN Code	4056418144498
Module Capacity	24
Trunk Capacity	24 (size 1 or 2, double stack cradle)

## Shipping Information

Units per Delivery	1/1
Packaging Dimensions (W x D x H)	565 mm x 660 mm x 216 mm (22.3 in x 27.4 in x 8.4 in)
Shipping Weight	10.9 kg (24 lb)



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • [www.corning.com/opcomm](http://www.corning.com/opcomm)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/trademarks](http://www.corning.com/opcomm/trademarks). All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2016 Corning Optical Communications. All rights reserved.

Corning Optical Communications RF LLC (Corning Gilbert) • 5310 W. Camelback Rd. • Glendale, AZ 85301 USA

800-528-5567 • FAX: 800-344-6356 • International: +1-623-245-1050 • [www.corning.com/opcomm](http://www.corning.com/opcomm)

Page 3 | Revision date 2016-03-03

A complete listing of the trademarks of Corning Optical Communications RF is available at [www.corning.com/opcomm/trademarks](http://www.corning.com/opcomm/trademarks). All other trademarks are the properties of their respective owners. Corning Optical Communications RF is ISO 9001

