

FutureCom™ Industrial Patch Cord, FRNC, 2x IP67/65 connector

purple, 2x IP67/65

CORNING

FutureCom™ Industrial S/FTP flex IP67/65 patch cords are specially designed for Ethernet connections in areas with harsh environmental conditions such as humidity, water, dust or extreme temperatures.

The FutureCom Industrial S/FTP flex IP67/65 patch cord are foil and braid shielded (PiMF) and offer a polyurethane jacket for harsh environments. They are assembled with two industrial IP67/65 connector in compliance with IEC 60603-7-4 and IEC 61076-3-106 and one RJ45 connector at each end.

They are available in various lengths.

Features

- high-quality IP67 industrial-RJ45 Cat.6 connector in compliance with IEC 61076-3-106
- Robust connector for harsh environmental conditions such as jet water during cleaning with water hose, extreme temperatures, dust and humidity
- Flame resistant and non-corrosive
- Microbe- and hydrolysis resistant cable
- Cable resistant against mineral and cooling lubricant
- Cable resistant against aromatic hydrocarbon
- IP67 protection level according to EN 60529
- ProfiNET compliant



Specifications

General Specifications	
Cable Assembly Type	Industrial Patch Cords
Environment	Industrial
Cable Type	S/FTP
Halogen-free	Yes
Category	6

Design - Connector A	
Connector Type	IP67

FutureCom™ Industrial Patch Cord, FRNC, 2x IP67/65 connector

purple, 2x IP67/65

CORNING

Mechanical Specifications - Connector A

Durability	750 Cycles
------------	------------

Electrical Specifications - Connector

Insulation Resistance	$\geq 5000 \text{ M}\Omega$
-----------------------	-----------------------------

Design - Connector B

Copper Connector Type - B	IP67
---------------------------	------

Cable Design

Min. Bend Radius Installation	40 mm
Min. Bend Radius Operation	30 mm
Outer Jacket Material	LSZH™/FRNC
Outer Jacket Colour	Purple

Mechanical Characteristics

Copper conductor	AWG 26
Temperature range (installation)	0 °C to 50 °C
Operating temperature	-20 °C to 60 °C

Electrical characteristics (at 20°C)

Max. loop resistance	290 Ω /km
DC resistance unbalance	2 %
Impedance Z_0 at 0-100 MHz	100 Ω +/- 15%
Impedance Z_0 at 101-250 MHz	100 Ω +/- 18%
Impedance z_0 at 251-600 MHz	100 Ω +/- 25%
Surface transfer impedance	< 10 m Ω /m per meter at 10 MHz
Mutual capacity	43 pF/m
Earth coupling at 0.001 MHz	1600
Propagation delay ≥ 10 MHz	4.3 ns/m
Delay skew	20 ns/100 m

FutureCom™ Industrial Patch Cord, FRNC, 2x IP67/65 connector

purple, 2x IP67/65

CORNING

Chemical characteristics

RoHS	Free of hazardous substances according to RoHS 2002/95/EG
------	---

Ordering Information

Part Number	CCAIHB-G70H2-A010-C0
Product Description	FutureCom™ Industrial Patch Cord, FRNC, IP67/65 - IP67/65 connector, purple, 1 m
EAN Code	4042673334491
Length	1 m

Shipping Information

Units per Delivery	1/1
--------------------	-----



Corning Optical Communications GmbH & Co. KG · Leipziger Strasse 121 · 10117 Berlin, GERMANY
00 800 2676 4641 · FAX: +49 30 5303 2335 · www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2014 Corning Optical Communications. All rights reserved.