

EDGE™ Trunk Cable

50 µm multimode (OM4), MTP® Connector to MTP Connector, 72 F, with 33/33 inch legs, pulling grip one side, 100 ft

CORNING

EDGE™ MTP® trunks provide the backbone of the EDGE Solution. With non-pinned MTP connectors on both ends of the cable, the trunks are designed to interface with EDGE or Plug & Play™ modules. All trunks are shipped with strain-relief clips that allow for tool-less installation in both EDGE and Plug & Play housings. The trunks conform to TIA-568 Type-B polarity.

Features and Benefits

High-density trunk cables

Allow tighter trunk cable bends for slack storage and routing

Low insertion loss performance

Allows for more connections in a link when deploying a TIA-942-compliant system

Universal wired components

Enable moves, adds and changes without polarity concerns; provide a simple migration path between 2-fiber and parallel optic applications

Factory-terminated solutions

Provide consistent quality, ensure system performance, and reduce installation time



Standards

Approvals and Listings NFPA 262, National Electrical Code® (NEC®), OFNP, CSA FT-6

Specifications

| General Specifications | |
|------------------------|----------------------------|
| Application | Data Center LAN/SAN |
| Cable Type | Indoor; ANSI/ICEA S-83-596 |
| Flame Rating | Plenum (OFNP) |
| Cable Assembly Type | EDGE™ Trunk |
| Fiber Category | 50 µm MM (OM4) |

EDGE™ Trunk Cable

50 µm multimode (OM4), MTP® Connector to MTP Connector, 72 F, with 33/33 inch legs, pulling grip one side, 100 ft



Temperature Range

| | |
|-----------|-----------------------------------|
| Operation | -10 °C to 60 °C (14 °F to 140 °F) |
|-----------|-----------------------------------|

Design - Connector A

| | |
|------------------|-------------------|
| Connector Type | MTP® (non-pinned) |
| Ferrule Material | Composite |

Optical Specifications - Connector A

| | |
|----------------------|----------|
| Insertion Loss, Max. | 0.25 dB |
| Reflectance | < -20 dB |

Design - Connector B

| | |
|------------------|-------------------|
| Connector Type | MTP® (non-pinned) |
| Ferrule Material | Composite |

Optical Specifications - Connector B

| | |
|----------------------|----------|
| Insertion Loss, Max. | 0.25 dB |
| Reflectance | < -20 dB |

Cable Design

| | |
|----------------------------|---------------------------|
| Fiber Count | 72 |
| Outer Jacket Color | Aqua |
| Polarity | Universal; TIA-568 Type-B |
| Strain-Relief Bracket Type | 2 |

Mechanical Characteristics Cable

| | |
|--|----------------------------|
| Nominal Outer Diameter | 10.5 mm ± 0.3 mm (0.41 in) |
| Min. Bend Radius Installation | 157.5 mm (6.2 in) |
| Min. Bend Radius Operation | 52.5 mm (2.07 in) |
| Max. Tensile Strength for Installation | 660 N |

EDGE™ Trunk Cable

50 µm multimode (OM4), MTP® Connector to MTP Connector, 72 F, with 33/33 inch legs, pulling grip one side, 100 ft



Mechanical Characteristics Cable

| | |
|---------------------------------------|--------------------------|
| Weight | 95 kg/km (64 lb/1000 ft) |
| Minimum Conduit Size with 18-in Elbow | 3.0 in |

Furcation - Connector A

| | |
|--------------------|---|
| Leg Length | 838 mm (-0 mm/+76 mm) (33 in (-0 in/+3 in)) |
| Leg Color | Aqua |
| Leg Diameter | 2.0 mm |
| Furcation Type - A | EDGE™ Size 2; 20 mm x 20 mm x 108.6 mm |

Furcation - Connector B

| | |
|--------------------|---|
| Leg Length | 838 mm (-0 mm/+76 mm) (33 in (-0 in/+3 in)) |
| Leg Color | Aqua |
| Leg Diameter | 2.0 mm |
| Furcation Type - B | EDGE™ Size 1; 14.7 mm x 14.7 mm x 108.6 mm |

Pulling Grip - Connector A

| | |
|-----------------------------|----------------|
| Pulling Grip - Connector A | Yes |
| Pulling Grip Outer Diameter | 56 mm (2.2 in) |
| Min. Duct Size Diameter | 89 mm (3.5 in) |
| Tensile Strength | 440 N (100 lb) |

Pulling Grip - Connector B

| | |
|----------------------------|----|
| Pulling Grip - Connector B | No |
|----------------------------|----|

Chemical Characteristics

| | |
|------|---|
| RoHS | Free of hazardous substances according to RoHS 2011/65/EU |
|------|---|

EDGE™ Trunk Cable

50 µm multimode (OM4), MTP® Connector to MTP Connector, 72 F, with 33/33 inch legs, pulling grip one side, 100 ft

CORNING

Fiber Specifications

| Optical Characteristics (cabled) | |
|---|---|
| Fiber Type | Multimode |
| Fiber Core Diameter | 50 µm |
| Fiber Category | OM4 Extended Distance |
| Fiber Compliance | IEC 60793-2-10 for A1a class 50/125 multimode fibers; TIA/EIA 492AAAD (OM4); ITU-T Recommendation G.651; ISO/IEC 11801 Ed.2.2 Grade OM4 |
| Wavelengths | 850 nm / 1300 nm |
| Maximum Attenuation | 2.8 dB/km / 1.0 dB/km |
| Min. Overfilled Launch (OFL) Bandwidth | 1500 MHz*km / 500 MHz*km |
| Minimum Effective Modal Bandwidth (EMB) | 4700 MHz*km / - |
| Serial 1 Gigabit Ethernet | 1000 m / 600 m |
| Serial 10 Gigabit Ethernet | 600 m / - |
| Standards in Compliance | TIA/EIA 492AAAC-A, Tested with minEMBc method to TIA/EIA 455-220, IEC 60793-2-10 Type A1a.2 Ed.2.0 and IEC 60793-1-49 Ed.2.0, ITU-T G651, ISO/IEC 11801 Ed.2.2 Cat. OM3 |
| Fiber Code | Q |
| Induced Attenuation @ 7.5 mm Radius | < 0.2 dB / - |

- Notes: 1) 50 µm multimode fiber macrobend loss ≤ 0.2 dB at 850 nm for two turns around 7.5 mm radius mandrel.
2) Meets 0.75 ns optical skew when used in all Corning Plug and Play™/EDGE™ systems solutions.
3) Improved attenuation and bandwidth options available.
4) Bend-insensitive single-mode fibers available on request.
5) Contact a Corning Customer Care Representative for additional information.

Ordering Information

| | |
|---------------------|--|
| Part Number | G757572QPNDU100F |
| Product Description | EDGE™ Solutions Trunk Cable, 50 µm multimode (OM4), MTP® Connector to MTP Connector, 72 F, with 33/33 inch legs, pulling grip one side, 100 ft |
| EAN Code | 4056418144474 |
| Weight | 4.4 kg (9.6 lb) |
| Length | 100 ft (-0 ft/+2 ft) (30 m (-0 m/+0.61 m)) |

Shipping Information

| | |
|--------------------|---------|
| Units per Delivery | 1/1 |
| Reel Diameter | 23.5 in |
| Reel Width | 5 in |

EDGE™ Trunk Cable

50 µm multimode (OM4), MTP® Connector to MTP Connector, 72 F, with 33/33 inch legs, pulling grip one side, 100 ft

The CORNING logo is displayed in white, uppercase letters within a solid blue square.

Notes



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks.

All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2016 Corning Optical Communications. All rights reserved.