

EDGE™ Trunk Cable

SM (OS2), MTP® (NP) to MTP (NP), 288F, with 33/33-in legs, non-armored EDGE, plenum, pulling grip one end, 100 ft

CORNING

EDGE™ MTP® trunks provide the backbone of the EDGE Solution. With non-pinned MTP connectors on both ends of the cable, the trunks are designed to interface with EDGE or Plug & Play™ modules. All trunks are shipped with strain-relief clips that allow for tool-less installation in both EDGE and Plug & Play housings. The trunks conform to TIA-568 Type-B polarity.

Features and Benefits

High-density trunk cables

Allow tighter trunk cable bends for slack storage and routing

Low insertion loss performance

Allows for more connections in a link when deploying a TIA-942-compliant system

Universal wired components

Enable moves, adds and changes without polarity concerns; provide a simple migration path between 2-fiber and parallel optic applications

Factory-terminated solutions

Provide consistent quality, ensure system performance, and reduce installation time

Standards

Approvals and Listings NFPA 262, National Electrical Code® (NEC®), OFNP, CSA FT-6

Specifications

General Specifications	
Application	Data Center LAN/SAN
Cable Type	Indoor: ANSI/ICEA S-83-596
Flame Rating	Plenum (OFNP)
Cable Assembly Type	EDGE™ Trunk
Fiber Category	Bend-improved SM (OS2)

EDGE™ Trunk Cable

SM (OS2), MTP® (NP) to MTP (NP), 288F, with 33/33-in legs, non-armored EDGE, plenum, pulling grip one end, 100 ft

CORNING

Temperature Range

Operation	-10 °C to 60 °C (14 °F to 140 °F)
-----------	-----------------------------------

Design - Connector A

Connector Type	MTP® (non-pinned)
Ferrule Material	Composite

Optical Specifications - Connector A

Reflectance, Typical	< -55 dB
Insertion Loss, Max.	0.35 dB

Design - Connector B

Connector Type	MTP® (non-pinned)
Ferrule Material	Composite

Optical Specifications - Connector B

Reflectance, Typical	< -55 dB
Insertion Loss, Max.	0.35 dB

Cable Design

Fiber Count	288
Outer Jacket Color	Yellow
Polarity	Universal; TIA-568 Type-B

Mechanical Characteristics Cable

Nominal Outer Diameter	16.0 mm (0.63 in)
Min. Bend Radius Installation	240 mm (9.5 in)
Min. Bend Radius Operation	80.0 mm (3.2 in)
Max. Tensile Strength for Installation	440 N
Weight	237.7 kg/km (156 lb/1000 ft)

EDGE™ Trunk Cable

SM (OS2), MTP® (NP) to MTP (NP), 288F, with 33/33-in legs, non-armored EDGE, plenum, pulling grip one end, 100 ft

CORNING

Optical Characteristics (cabled)

Fiber Compliance	ITU-T G.652.D and ITU-T G.657.A1
Wavelengths	1550 nm / 1383 nm / 1550 nm
Maximum Attenuation	0.4 dB/km / 0.4 dB/km / 0.3 dB/km
Serial 1 Gigabit Ethernet	5000 m / - / -
Serial 10 Gigabit Ethernet	10000 m / - / 40000 m
Induced Attenuation @ 7.5 mm Radius	0.5 dB 1 turn; 10 mm radius; 1550 nm

Furcation - Connector A

Leg Length	838 mm (+76 mm/-0 mm) (33 in (+3 in/-0 in))
Leg Diameter	2.0 mm
Leg Color	Yellow

Furcation - Connector B

Leg Length	838 mm (+76 mm/-0 mm) (33 in (+3 in/-0 in))
Leg Diameter	2.0 mm
Leg Color	Yellow

Pulling Grip - Connector A

Pulling Grip - Connector A	Yes
Pulling Grip Outer Diameter	38.1 mm (1.5 in)
Min. Duct Size Diameter	50.0 mm (2.0 in)
Tensile Strength	440 N (100 lb)

Pulling Grip - Connector B

Pulling Grip - Connector B	No
----------------------------	----

Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

EDGE™ Trunk Cable

SM (OS2), MTP® (NP) to MTP (NP), 288F, with 33/33-in legs, non-
armored EDGE, plenum, pulling grip one end, 100 ft



Ordering Information

Part Number	G9090U8GPNDU100F
Product Description	EDGE™ Solutions Trunk Cable, SM (OS2), MTP® (NP) to MTP (NP), 288F, with 33/33-in legs, non-armored EDGE, plenum, pulling grip one end, 100 ft
EAN Code	4056418687872
Length	100 ft (+3 ft/-0 ft) (30.5 m (+0.91 m/-0 m))

Shipping Information

Units per Delivery	1/1
--------------------	-----



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2017 Corning Optical Communications. All rights reserved.

