

LANC Housing, loaded, with pigtails, LC Duplex

96 fibres, 1U, 50 µm MM (OM4), with MFT tray for up to 24 heat shrink splice protectors, w/o splice protectors, black

CORNING

The LANC product family offers an economic solution for the basic cabling requirements of local area networks. The fixed LANscape® LANC housing can be equipped with industry common adapter types in different fibre categories and provides room for up to 48 fibres (24 ports) LC Duplex connectivity. The housing is suitable for direct field-termination as well as fusion splicing with pigtails. Two dual cable entries in the back of the housing can accommodate cable glands and has an easy to remove cover.

Enabling a simple exchange of adapter modules during moves, adds and changes (MACs) the modular housings reduce the risk of network disruptions.

Features and Benefits

Modular front allows to exchange and mix different adapter types and fibre categories

Capacity up to max. 24 fibres (12 Ports) for ST Simplex or SC Duplex

Quick-mount feature allows for easy and accurate single-person installation

Port numbering above and below the ports

Space above the ports can be used for customised labelling


Suitable for field-termination and fusion splicing with pigtails

Low installation depth allow for housing to be mounted in shallow cabinets or racks

Available empty (1U) or preloaded with or without pigtails



Part Number: LANC-196-AD-03Q-S1B



Part Number: LANC-196-AD-03Q-S1B

LANC Housing, loaded, with pigtails, LC Duplex

96 fibres, 1U, 50 µm MM (OM4), with MFT tray for up to 24 heat shrink splice protectors, w/o splice protectors, black



Specifications

General Specifications	
Application	Splicing
Mounting type	Rack 19"
Mounting Technology	Flush mount
Access type	Front access fixed
Fibre Category	50 µm MM (OM4)
Lockable	No

Temperature Range	
Operation	-10 °C to 60 °C
Storage	-10 °C to 60 °C

Design - Hardware	
Housing material	High-grade steel
Housing Colour	Black
Height Unit	1U
Fibre count	96
Cable entry type	slotted for cable glands, straight
Number of Ports	48
Number of adapters	48
Number of pigtails	96
Number of pigtail bundles	8
Pigtail length	2 m
Connector type	LC
Pigtail Type	Bundle colour coded to telcordia on primary and secondary coating
Number of splice trays	4
Splice tray type	MFT
Splice Protectors Type	Heat-shrink

Mechanical Characteristics	
Dimensions (HxWxD)	43.6 mm x 483 mm x 210.4 mm
Weight	2.60 kg

LANC Housing, loaded, with pigtails, LC Duplex

96 fibres, 1U, 50 µm MM (OM4), with MFT tray for up to 24 heat shrink splice protectors, w/o splice protectors, black



Optical Specification - Hardware

Insertion loss, max.	0.5 dB
----------------------	--------

Design Adapter

Adapter type	LC duplex shuttered
Adapter housing material	Composite
Adapter housing colour	Turquoise
Insert Material	Ceramic
Keyed adapter	No
Shuttered adapter	Yes

Ordering Information

Part Number	LANC-196-AD-03Q-S1B
Product Description	LANC Housing, loaded, with pigtails, 48 LC Duplex shuttered, 1U, turquoise OM4, with MFT tray for up to 24 heat shrink splice protectors, w/o splice protectors, black
EAN Code	4056418019383

Shipping Information

Packing dimensions (L x W x H)	550 mm x 360 mm x 60 mm
Shipping Weight	3.55 kg
Units Per Delivery	1/1



Corning Optical Communications GmbH & Co. KG · Leipziger Strasse 121 · 10117 Berlin, GERMANY
00 800 2676 4641 · FAX: +49 30 5303 2335 · www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified.
© 2017 Corning Optical Communications. All rights reserved.